

SUMMARY OF OECD TEST 2948-NEBRASKA SUMMARY 1030 CHALLENGER MT555E TECHSTAR DIESEL CONTINUOUSLY VARIABLE TRANSMISSION

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Diesel Consumption		D.E.F. Consumption		Mean Atmospheric Conditions
		Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.l/l)	Gal/hr (l/h)	
MAXIMUM POWER AND FUEL CONSUMPTION						
Rated Engine Speed—(PTO speed—1103 rpm)						
161.1 (120.1)	2099	9.14 (34.58)	0.397 (0.241)	17.63 (3.47)	0.59 (2.25)	
Standard Power Take-off Speed (1001 rpm)						
181.3 (135.2)	1905	9.81 (37.14)	0.378 (0.230)	18.48 (3.64)	0.62 (2.34)	
Maximum Power (1 hour)						
184.7 (137.7)	1800	9.83 (37.20)	0.372 (0.226)	18.79 (3.70)	0.66 (2.51)	
VARYING POWER AND FUEL CONSUMPTION						
161.1 (120.1)	2099	9.14 (34.58)	0.397 (0.241)	17.63 (3.47)	0.59 (2.25)	Air temperature
138.1 (103.0)	2118	8.00 (30.28)	0.405 (0.246)	17.26 (3.40)	0.55 (2.08)	72°F (22°C)
104.1 (77.6)	2126	6.40 (24.21)	0.429 (0.261)	16.27 (3.21)	0.46 (1.73)	Relative humidity
69.6 (51.9)	2134	4.90 (18.54)	0.492 (0.299)	14.20 (2.80)	0.34 (1.28)	71%
34.9 (26.0)	2140	3.37 (12.77)	0.675 (0.411)	10.36 (2.04)	0.25 (0.95)	Barometer
---	2151	2.16 (8.16)	---	---	---	30.4" Hg (102.8 kPa)

Maximum torque - 595 lb.-ft. (807 Nm) at 1448 rpm
 Maximum torque rise - 47.7%
 Torque rise at 1700 engine rpm - 35%
 Power increase at 1800 engine rpm - 14%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption		Temp. °F (°C)		Barom. inch Hg (kPa)
					lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.l/l)	cool- ing med	Air dry bulb	
Power at Rated Engine Speed—Turtle 8									
129.5 (96.6)	10140 (45.1)	4.79 (7.71)	2097	5.2	0.506 (0.308)	13.81 (2.72)	194 (90)	34 (1)	30.1 (102.0)
75% of Pull at Rated Engine Speed—Turtle 8									
99.9 (74.5)	7600 (33.8)	4.93 (7.93)	2122	2.5	0.532 (0.324)	13.15 (2.59)	189 (87)	34 (1)	30.1 (102.0)
50% of Pull at Rated Engine Speed—Turtle 8									
68.1 (50.8)	5125 (22.8)	4.99 (8.03)	2128	1.5	0.615 (0.374)	11.37 (2.24)	189 (87)	34 (1)	30.1 (102.0)
75% of Pull at Reduced Engine Speed—Turtle 10									
99.5 (74.2)	7555 (33.6)	4.94 (7.94)	1376	2.3	0.465 (0.283)	15.02 (2.96)	183 (84)	36 (2)	30.1 (101.9)
50% of Pull at Reduced Engine Speed—Turtle 10									
67.7 (50.5)	5105 (22.7)	4.98 (8.01)	1384	1.7	0.500 (0.304)	13.99 (2.76)	181 (83)	36 (2)	30.1 (101.9)

Location of tests: IRSTEA, Centre d'Antony, 1 rue Pierre-Giles de Gennes, CS 10030 92761 Antony, Cedex France

Dates of tests: February, 2016

Manufacturer: AGCO S.A. ZA, n2, BP 60307, Avenue Blaise Pascal, 60026 Beauvais, Cedex, France

CONSUMABLE FLUIDS : Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.838 Fuel weight 6.98 lbs/gal (0.836 kg/l) Diesel Exhaust Fluid (DEF) 32% aqueous urea solution DEF weight 9.08 lbs/gal (1.091 kg/l) Oil SAE 15W40 API service classification CJ-4 Transmission and hydraulic lubricant BP Terrac Tractan 9 10W/40 Front axle lubricant SAE 85W140 API GL-5

ENGINE: Make AGCO Power Diesel Type six cylinder vertical with turbocharger, air to air intercooler and SCR (selective catalyst reduction) technology Serial No. Z0018 Crankshaft lengthwise Rated engine speed 2100 Bore and stroke 4.252" x 4.724" (108.0 mm x 120.0 mm) Compression ratio 17.4 to 1 Displacement 402 cu in (6596 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil Fuel filter one paper element Muffler underhood Exhaust vertical Cooling medium temperature control thermostat and variable speed fan

CHASSIS: Type front wheel assist Serial No. D 242 901 Tread width rear 52.8" (1340 mm) to 87.8" (2230 mm) front 52.8" (1340 mm) to 87.8" (2230 mm) Wheelbase 117.0" (2973 mm) Hydraulic control system direct engine drive Transmission CVT. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. Nominal travel speeds mph (km/h) forward: Low range 0-19 (0-30), high range 0-25 (0-40) reverse: Low range 0-19 (0-30), high range 0-19 (0-30) Clutch a foot pedal controls the hydrostatic oil flow Brakes multiple wet disc hydraulically operated by two foot pedals that can be locked together Steering hydrostatic Power take-off 540 rpm at 1868 engine rpm or 1000 rpm at 1903 engine rpm Unladen tractor mass 18180 lb (8250 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER AT SELECTED TRAVEL SPEEDS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. ^o F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Turtle 3									
72.3 (53.9)	16095 (71.6)	1.68 (2.71)	2126	14.6	0.618 (0.376)	11.32 (2.23)	181 (83)	34 (1)	30.2 (102.1)
Turtle 4.5									
99.8 (74.4)	15940 (70.9)	2.35 (3.78)	2114	11.8	0.589 (0.358)	11.88 (2.34)	187 (86)	34 (1)	30.2 (102.1)
Turtle 6.5									
146.3 (109.1)	15060 (67.0)	3.64 (5.86)	1794	8.1	0.477 (0.290)	14.67 (2.89)	185 (85)	34 (1)	30.1 (102.0)
Turtle 8									
152.2 (113.5)	11960 (53.2)	4.77 (7.68)	1837	6.3	0.459 (0.279)	15.23 (3.00)	196 (91)	34 (1)	30.1 (102.0)
Turtle 10									
153.0 (114.1)	9420 (41.9)	6.09 (9.80)	1835	4.9	0.453 (0.276)	15.43 (3.04)	189 (87)	36 (2)	30.1 (102.0)
Turtle 13									
145.6 (108.6)	7015 (31.2)	7.79 (12.54)	1805	3.2	0.472 (0.287)	14.82 (2.92)	192 (89)	37 (3)	30.1 (101.8)
Turtle 15									
141.3 (105.3)	5880 (26.2)	9.01 (14.50)	1788	2.4	0.483 (0.294)	14.47 (2.85)	199 (93)	37 (3)	29.9 (101.2)
Rabbit 9									
134.1 (100.0)	9710 (43.2)	5.18 (8.34)	1811	3.4	0.515 (0.313)	13.57 (2.67)	198 (92)	41 (5)	30.0 (101.6)
Rabbit 12									
144.4 (107.7)	7485 (33.3)	7.23 (11.64)	1821	2.4	0.475 (0.289)	14.72 (2.90)	199 (93)	39 (4)	30.0 (101.6)
Rabbit 15									
146.6 (109.3)	6055 (26.9)	9.08 (14.61)	1810	1.9	0.472 (0.287)	14.82 (2.92)	196 (91)	37 (3)	30.0 (101.6)
Rabbit 17									
142.0 (105.9)	5165 (23.0)	10.31 (16.59)	1819	1.5	0.494 (0.301)	14.15 (2.79)	198 (92)	37 (3)	30.0 (101.6)
Rabbit 20									
135.8 (101.3)	4170 (18.6)	12.21 (19.65)	1786	1.2	0.510 (0.310)	13.71 (2.70)	198 (92)	37 (3)	30.0 (101.6)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

NOTE: The data on this summary was obtained from OECD report 2948 conducted on the Massey Ferguson 7719 Dyna VT Diesel.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's 3 point lift claim of 16700 lbs (7575 kg). The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2948**, Nebraska Summary 1030, June 16, 2016.

Roger M. Hoy
 Director

M.F. Kocher
 S.K. Pitla
 J.D. Luck
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front wheel drive	
	Engaged dB(A)	Disengaged dB(A)
At no load in Turtle 8	70.0	70.0
Bystander		--

TIRES, BALLAST AND WEIGHT

Rear Tires - No., size, ply & psi(kPa)
Front Tires - No., size, ply & psi(kPa)
Height of Drawbar
Static Weight with operator - Rear
 - Front
 - Total

Tested without ballast

Two 620/70R42;**,15(100)
 Two 480/70R30;**,15(100)
 19.7 in (500 mm)
 10770 lb (4885 kg)
 7585 lb (3440 kg)
 18355 lb (8325 kg)

HYDRAULIC PERFORMANCE

CATEGORY: III

Quick Attach: None

OECD Static test

Maximum force exerted through whole range: 15105 lbs (67.2 kN)

i) Sustained pressure of the open relief valve: 2870 psi (198 bar)

Standard Pump	Optional pump
29 GPM (110 l/min)	50 GPM (190 l/min)
<u>two outlet sets combined</u>	<u>two outlet sets combined</u>
29.9 GPM (113.0 l/min)	52.5 GPM (198.8 l/min)

ii) Pump delivery rate at minimum pressure:

iii) Pump delivery rate at maximum

hydraulic power:	27.8 GPM (105.3 l/min)	47.6 GPM (180.2 l/min)
Delivery pressure:	2490 psi (172 bar)	1855 psi (128 bar)
Power:	40.3 HP (30.0 kW)	51.5 HP (38.4 kW)

ii) Pump delivery rate at minimum pressure:

iii) Pump delivery rate at maximum

hydraulic power:	26.9 GPM (101.9 l/min)	30.0 GPM (113.8 l/min)
Delivery pressure:	2235 psi (154 bar)	2110 psi (146 bar)
Power:	35.1 HP (26.2 kW)	37.0 HP (27.6 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	29.8	756
B	15.7	400
C	16.5	419
D	14.0	355
E	8.8	223
F	10.9	276
G	36.4	925
H	2.4	60
I	18.5	471
J	25.5	649
K	27.4	696
L	46.9	1192
M	23.6	600
N	39.5	1003
O	9.0	229
P	52.5	1334
Q	40.2	1020
R	33.1	840

