

SUMMARY OF OECD TESTS 2278 and 2319—NEBRASKA SUMMARY 531

CASE IH JX 1100U DIESEL

12 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed (PTO speed—1050 rpm)					
87.3 (65.1)	2500	5.62 (21.27)	0.451 (0.275)	15.53 (3.06)	
Maximum Power (2 hours)					
88.1 (65.7)	2400	5.51 (20.85)	0.438 (0.267)	15.99 (3.15)	
Standard Power Take-off speed (1008 rpm)					
88.1 (65.7)	2400	5.51 (20.85)	0.438 (0.267)	15.99 (3.15)	
VARYING POWER AND FUEL CONSUMPTION					
87.3 (65.1)	2500	5.62 (21.27)	0.451 (0.275)	15.53 (3.06)	Air temperature
78.2 (58.3)	2619	5.41 (20.49)	0.485 (0.295)	14.47 (2.85)	75°F (24°C)
58.7 (43.8)	2631	4.38 (16.57)	0.523 (0.318)	13.40 (2.64)	Relative humidity
39.3 (29.3)	2636	3.64 (13.79)	0.649 (0.395)	10.80 (2.13)	50%
19.7 (14.7)	2652	2.82 (10.68)	1.001 (0.609)	7.00 (1.38)	Barometer
--	2664	2.08 (7.87)	--	--	29.4" Hg (99.4 kPa)
Maximum Torque -269.6 lb.-ft. (365.5 Nm) at 1400 rpm					
Maximum Torque rise -47.1%					
Torque rise at 2000 engine rpm -21%					

Location of tests: Istituto Per La Macchine Agricole
E Movimento Terra, Strada delle Cacce, 73-10135
Torino, Italy

Dates of tests: September 2004

Manufacturer: CNH America LLC, 700 State St.
Racine, Wi. 53404 USA

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.842
Fuel weight 7.01 lbs/gal (0.840 kg/l) **Oil SAE** 15W40
API service classification CH-4 **Oil consumption for 10 hours** 0.03 lb (15 gm) **Transmission and hydraulic lubricant** Ambra Multi G **Front axle lubricant** Ambra Multi G

ENGINE: Make CNH Diesel **Type** four cylinder vertical with turbocharger **Serial No.** 00116282
Crankshaft lengthwise **Rated Engine speed** 2500
Bore and stroke 4.094" x 5.197" (104.0 mm x 132.0 mm) **Compression ratio** 17.5 to 1 **Displacement** 274 cu in (4485 ml) **Starting system** 12 volt
Lubrication pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: **Type** 2WD and front wheel assist **Serial No.** HJT002764 **Tread width** rear 68.2" (1732 mm) to 83.9" (2132 mm) front: 2WD - 55.4" (1407 mm) to 85.6" (2175 mm), FWA - 56.1" (1425 mm) to 84.0" (2133 mm) **Wheel base** 2WD - 92.2" (2342 mm) FWA - 91.1" (2314 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio **Nominal travel speeds mph (km/h)** first 1.41 (2.27) second 2.05 (3.30) third 2.96 (4.76) fourth 3.30 (5.31) fifth 4.24 (6.82) sixth 4.79 (7.71) seventh 6.88 (11.07) eighth 7.76 (12.49) ninth 9.90 (15.93) tenth 11.28 (18.16) eleventh 16.27 (26.18) twelfth 23.30 (37.50) reverse 1.41 (2.27), 2.05 (3.30), 2.96 (4.76), 3.30 (5.31), 4.24 (6.82), 4.79 (7.71), 6.88 (11.07), 7.76 (12.49), 9.90 (15.93), 11.28 (18.16), 16.27 (26.18), 23.30 (37.50) **Clutch** dual dry disc operated by foot pedal **Brakes** wet disc hydraulically operated by two foot pedals which can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2199 engine rpm or 1000 rpm at 2381 engine rpm **Unladen tractor mass** 2WD - 8565 lb (3885 kg), FWA - 8930 lb (4050 kg)

**DRAWBAR PERFORMANCE(40 km/h trans.)
BALLASTED - FRONT DRIVE ENGAGED
FUEL CONSUMPTION CHARACTERISTICS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
75% of Pull at Maximum Power—Five Hours 6th (2 Med) Gear									
59.5 (44.4)	4490 (20.0)	4.97 (8.00)	2609	3.0	0.639 (0.389)	10.96 (2.16)	196 (91)	73 (23)	29.4 (99.5)
MAXIMUM POWER IN SELECTED GEARS									
2nd (2 Lo) Gear									
48.7 (36.3)	10125 (45.0)	1.80 (2.90)	2630	15.0	0.645 (0.392)	10.87 (2.14)	192 (89)	73 (23)	29.4 (99.4)
3rd (3 Lo) Gear									
66.0 (49.2)	9720 (43.2)	2.54 (4.10)	2400	9.0	0.585 (0.356)	11.98 (2.36)	194 (90)	75 (24)	29.4 (99.4)
4th (1 Med) Gear									
70.3 (52.4)	9015 (40.1)	2.92 (4.70)	2395	7.0	0.550 (0.334)	12.75 (2.51)	192 (89)	77 (25)	29.4 (99.4)
5th (4 Lo) Gear									
70.0 (52.2)	6925 (30.8)	3.79 (6.10)	2402	4.7	0.550 (0.335)	12.74 (2.51)	196 (91)	75 (24)	29.4 (99.4)
6th (2 Med) Gear									
70.4 (52.5)	6070 (27.0)	4.35 (7.00)	2405	4.1	0.550 (0.334)	12.75 (2.51)	197 (92)	75 (24)	29.4 (99.4)
7th (3 Med) Gear									
69.9 (52.1)	4095 (18.2)	6.40 (10.30)	2400	2.4	0.552 (0.336)	12.69 (2.50)	196 (91)	77 (25)	29.4 (99.4)
8th (1 Hi) Gear									
70.3 (52.4)	3595 (16.0)	7.33 (11.80)	2402	2.1	0.548 (0.334)	12.78 (2.52)	194 (90)	79 (26)	29.4 (99.4)
9th (4 Med) Gear									
66.6 (49.7)	2715 (12.1)	9.20 (14.80)	2408	1.8	0.580 (0.353)	12.08 (2.38)	192 (89)	77 (25)	29.4 (99.4)
10th (2 Hi) Gear									
64.6 (48.2)	2295 (10.2)	10.56 (17.00)	2400	1.2	0.598 (0.363)	11.73 (2.31)	197 (92)	75 (24)	29.4 (99.4)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claim of 78.0 dB(A) cab sound level in the FWA mode. The manufacturer's 3 point lift claim of 6445 lbs (2923 kg) with EDC (electronic draft control) was not verified. The performance results on this summary were taken from OECD tests conducted under the Code I Test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **2278** and **2319**, Nebraska Summary 531, May 26, 2006.

Leonard L. Bashford
Director

M.F. Kocher
V.I. Adamchuk
J.A. Smith
Board of Tractor Test Engineers

FWA-(40 km/h trans)

	With Ballast	Without Ballast
TIRES, BALLAST AND WEIGHT		
Rear Tires	-No., size, ply & psi (kPa) Two 600/65R34; **,13 (90)	Two 600/65R34; **,13 (90)
Ballast	-Liquid (total) None	None
	-Cast Iron (total) 660 lb (300 kg)	None
Front Tires	-No., size, ply & psi (kPa) Two 480/65R24; **,17 (120)	Two 480/65R24; **,17 (120)
Ballast	-Liquid (total) None	None
	-Cast Iron (total) 1115 lb (505 kg)	None
Height of Drawbar	19.1 in (485 mm)	19.3 in (490 mm)
Static Weight with Operator - Rear	5735 lb (2600 kg)	5525 lb (2505 kg)
- Front	5135 lb (2330 kg)	3570 lb (1620 kg)
- Total	10870 lb (4930 kg)	9095 lb (4125 kg)

DRAWBAR PERFORMANCE(30 km/h trans.)

BALLASTED - 2WD

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Fuel Consumption Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
75% of Pull at Maximum Power—Five Hours 7th (3 Med) Gear									
58.1 (43.3)	3940 (17.5)	5.53 (8.90)	2618	4.5	0.654 (0.398)	10.71 (2.11)	192 (89)	68 (20)	29.0 (98.2)

MAXIMUM POWER IN SELECTED GEARS

6th (2 Med) Gear									
61.3 (45.7)	6720 (29.9)	3.42 (5.50)	2587	15.0	0.626 (0.381)	11.20 (2.21)	194 (90)	75 (24)	29.1 (98.6)
7th (3 Med) Gear									
69.7 (52.0)	5260 (23.4)	4.97 (8.00)	2397	6.5	0.553 (0.337)	12.67 (2.50)	190 (88)	73 (23)	29.1 (98.6)
8th (1 Hi) Gear									
68.5 (51.1)	4495 (20.0)	5.72 (9.20)	2402	5.5	0.563 (0.342)	12.45 (2.45)	189 (87)	72 (22)	29.1 (98.6)
9th (4 Med) Gear									
68.1 (50.8)	3485 (15.5)	7.33 (11.80)	2405	4.2	0.566 (0.344)	12.39 (2.44)	192 (89)	75 (24)	29.1 (98.6)
10th(2 Hi) Gear									
67.9 (50.6)	3035 (13.5)	8.39 (13.50)	2397	3.5	0.568 (0.346)	12.33 (2.43)	190 (88)	73 (23)	29.1 (98.6)

2WD-(30 km/h trans)

TIRES, BALLAST AND WEIGHT

	With Ballast	Without Ballast
Rear Tires	-No., size, ply & psi (kPa) Two 600/65R34;**,13 (90)	Two 600/65R34;**,13 (90)
Ballast	-Liquid (total) None	None
	-Cast Iron (total) 660 lb (300 kg)	None
Front Tires	-No., size, ply & psi (kPa) Two 10.00-16;8;35 (240)	Two 10.00-16; 8;35 (240)
Ballast	-Liquid (total) None	None
	-Cast Iron (total) 1115 lb (505 kg)	None
Height of Drawbar	19.1 in (485 mm)	19.3 in (490 mm)
Static Weight with Operator	-Rear 6270 lb (2845 kg)	5895 lb (2675 kg)
	-Front 4235 lb (1920 kg)	2835 lb (1285 kg)
	-Total 10505 lb (4765 kg)	8730 lb (3960 kg)

TRACTOR SOUND LEVEL WITH CAB	FWA dB(A)	2WD dB(A)
At no load in 6th (2 Med) gear	78.1	78.0
Bystander in 12th (4 Hi) gear	86.7	86.6

CENTER OF GRAVITY - 2WD

Horizontal distance forward from centerline of rear wheels	29.9" (760 mm)
Vertical distance above roadway	37.6" (955 mm)
Horizontal distance from center of rear wheel tread	0.0" (0 mm) to the left/right

CENTER OF GRAVITY - FWA

Horizontal distance forward from centerline of rear wheels	36.3" (923 mm)
Vertical distance above roadway	37.6" (955 mm)
Horizontal distance from center of rear wheel tread	0.0" (0 mm) to the left/right

TURNING ON A CONCRETE SURFACE (2WD)

Turning radius—without brake right 157" (4.00 m) left 157" (4.00 m)
Turning space radius—without brake right 161" (4.10 m) left 161" (4.10 m)

TURNING ON A CONCRETE SURFACE (FWA)

Turning radius—without brake right 209" (5.30 m) left 209" (5.30 m)
Turning space radius—without brake right 220" (5.60 m) left 220" (5.60 m)

THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum force exerted through whole range:	6025 lbs (26.8 kN)
i) Opening pressure of relief valve:	NA
Sustained pressure with relief valve open:	2800 psi (193 bar)
ii) Pump delivery rate at minimum pressure:	16.4 GPM (61.9 l/min)
iii) Pump delivery rate at maximum	
hydraulic power:	14.3 GPM (54.3 l/min)
Delivery pressure:	2450 psi (169 bar)
Power:	20.5 HP (15.3 kW)

	inch	mm
A	27.8	705
B	10.0	255
C	13.9	352
D	11.7	296
E	10.1	257
F	8.1	205
G	30.3	770
H	0.4	9
I	15.7	400
J	22.2	565
K	17.7	450
L	42.1	1070
M	21.6	548
N	37.0	940
O	7.9	200
P	46.3	1175
Q	34.8	885
R	25.2	640

HITCH DIMENSIONS AS TESTED—NO LOAD

