

# NEBRASKA TRACTOR TEST 2026

## JOHN DEERE 5093E LIMITED DIESEL

### 12 SPEED

#### CHASSIS SERIAL NUMBERS 340000 AND HIGHER

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					

Rated Engine Speed—(PTO speed—543 rpm)					
82.18 (61.28)	2398	5.53 (20.95)	0.474 (0.288)	14.85 (2.93)	
Maximum Power-(1 hour)					
87.33 (65.12)	2147	5.30 (20.07)	0.427 (0.260)	16.47 (3.24)	

#### VARYING POWER AND FUEL CONSUMPTION

82.18 (61.28)	2398	5.53 (20.95)	0.474 (0.288)	14.85 (2.93)	Air temperature
72.80 (54.29)	2510	5.34 (20.21)	0.516 (0.314)	13.64 (2.69)	73°F (23°C)
55.60 (41.46)	2534	4.54 (17.17)	0.574 (0.349)	12.26 (2.41)	Relative humidity
37.45 (27.93)	2560	3.48 (13.17)	0.653 (0.397)	10.77 (2.12)	32%
18.90 (14.09)	2580	2.57 (9.72)	0.956 (0.582)	7.36 (1.45)	Barometer
0.60 (0.45)	2597	1.67 (6.34)	19.625 (11.937)	0.36 (0.07)	28.82"Hg (97.63 kPa)

Maximum Torque 231 lb.-ft. (313 Nm) at 1749 rpm  
 Maximum Torque Rise -28.4%  
 Torque rise at 1900 rpm -27%  
 Power increase at 2147 rpm -6.3%

#### TRACTOR SOUND LEVEL WITH CAB

	Front Wheel Drive	
	Engaged dB(A)	Disengaged dB(A)
At no load in 6th(B2) gear	80.7	80.6
Transport in 12th(C4) gear		80.3
Bystander in 12th(C4) gear		84.3

#### TIRES AND WEIGHT

**Rear Tires**—No., size, ply & psi (kPa)  
**Front Tires**—No., size, ply & psi (kPa)  
**Height of Drawbar**  
**Static Weight with operator**—Rear  
 — Front  
 — Total

#### Tested Without Ballast

Two 18.4-30;8;12 (85)  
 Two 12.4-24;8;14 (95)  
 19.0 in (485 mm)  
 4405 lb (1998 kg)  
 3100 lb (1406 kg)  
 7505 lb (3404 kg)

**Location of tests:** Nebraska Tractor Test Laboratory, University of Nebraska, Lincoln Nebraska 68583-0832

**Dates of tests:** May 9 -17, 2012

**Manufacturer:** John Deere Commercial Products Inc., 700 Horizon South Parkway, Grovetown Ga. USA, 30813

**FUEL, OIL and TIME:** Fuel No. 2 Diesel Specific gravity converted to 60°/60° F (15°/15°C) 0.8448 Fuel weight 7.034 lbs/gal (0.843 kg/l) Oil SAE 15W40 API service classification CF/CH-4 Transmission and hydraulic lubricant John Deere Hy-Gard Fluid Front axle lubricant SAE 80W90 API GL-5 Total time engine was operated 6.0 hours

**ENGINE:** Make John Deere Diesel Type four cylinder vertical with turbocharger and air to air aftercooler Serial No. \*PE4045L861700\* Crankshaft lengthwise Rated engine speed 2400 Bore and stroke 4.19" x 5.00" (106.4 mm x 127.0 mm) Compression ratio 19.0 to 1 Displacement 276 cu in (4517 ml) Starting system 12 volt Lubrication pressure Air cleaner one paper element and one polyester felt element Oil filter one full flow cartridge Oil cooler radiator for transmission and hydraulic oil Fuel filter one paper element and sediment bowl Fuel cooler radiator for pump return fuel Muffler underhood Exhaust vertical Cooling medium temperature control one thermostat and variable speed fan

**ENGINE OPERATING PARAMETERS:** Fuel rate: 35.5 - 39.2 lb/h (16.1 - 17.8 kg/h) High idle: 2575 - 2650 rpm Turbo boost: nominal 10.9 - 13.8 psi (75 - 95 kPa) as measured 12.4 psi (85 kPa)

**CHASSIS:** Type front wheel assist Serial No. \*1LV5093EVCY440093\* Tread width rear 55.8" (1417 mm) to 71.7" (1820 mm) front 52.8" (1340 mm) to 75.0" (1904 mm) Wheelbase 85.7" (2178 mm) Hydraulic control system direct engine drive Transmission selective gear fixed ratio Nominal travel speeds mph (km/h) first 1.04 (1.68) second 1.42 (2.29) third 1.94 (3.13) fourth 2.60 (4.19) fifth 3.02 (4.86) sixth 4.11 (6.61) seventh 5.60 (9.02) eighth 7.51 (12.08) ninth 8.72 (14.04) tenth 11.87 (19.11) eleventh 16.20 (26.08) twelfth 21.71 (34.94) reverse 1.14 (1.84), 1.55 (2.50), 2.12 (3.41), 2.84 (4.57), 3.29 (5.30), 4.48 (7.21), 6.11 (9.84), 8.19 (13.18), 9.51 (15.31), 12.95 (20.84), 17.68 (28.45), 23.68 (38.11) Clutch single wet disc operated by foot pedal Brakes single wet disc hydraulically operated by two foot pedals which can be locked together Steering hydrostatic Power take-off 540 rpm at 2385 engine rpm or 540 rpm at 1710 engine rpm Unladen tractor mass 7330 lb (3325 kg)

## HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: None

OECD Static test

Maximum force exerted through whole range: 3213 lbs (14.3 kN)

i) Sustained pressure of the open relief valve: 2906 psi (200 bar)

ii) Pump delivery rate at minimum pressure and rated engine speed: 17.2 GPM (65.1 l/min)

iii) Pump delivery rate at maximum hydraulic power: 16.5 GPM (62.4 l/min)

Delivery pressure: 2507 psi (173 bar)

Power: 24.1 HP (18.0 kW)

## THREE POINT HITCH PERFORMANCE

Observed maximum pressure psi. (bar) 2830 (195)

Location: remote outlet

Hydraulic oil temperature: °F (°C) 148 (64)

Location: pump inlet

Category: II

Quick attach: none

### SAE Static Test—System pressure 2520 psi (174 Bar)

Hitch point distance to ground level in. (mm)	8.0 (203)	15.0 (381)	22.0 (559)	29.0 (737)	36.0 (914)
Lift force on frame lb	4694	4829	4685	4266	3596
" " " " " (kN)	(20.9)	(21.5)	(20.8)	(19.0)	(16.0)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**NOTE:** The performance figures on this report apply to tractors with chassis serial numbers 340000 and higher.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD, SAE and Nebraska test procedures. For the maximum power tests, the fuel temperature at the injection pump inlet was maintained at 105°F (40°C).


We, the undersigned, certify that this is a true and correct report of official Tractor Test No. **2026**, July 2, 2012.

Roger M. Hoy  
Director

M.A. Hanna  
P.J. Jasa  
J.D. Luck  
Board of Tractor Test Engineers

	SAE Test		OECD Test	
	inch	mm	inch	mm
A	23.2	590	24.1	613
B	11.0	280	11.0	280
C	14.0	356	14.0	356
D	12.2	311	12.2	311
E	11.2	284	11.2	284
F	6.5	165	6.5	165
G	27.4	695	27.4	695
H	0.2	4	0.2	4
I	15.1	384	15.1	384
J	20.9	530	20.9	530
K	16.7	424	16.7	424
L	39.2	996	39.2	996
M	22.4	570	22.4	570
N	32.9	836	32.9	836
O	8.0	203	8.0	203
P	40.9	1040	44.9	1140
Q	34.0	864	34.0	864
R	20.8	527	20.8	527

**HITCH DIMENSIONS AS TESTED - NO LOAD**



## Shiftable PTO Performance

### Economy mode

540 PTO rpm @ 1720 engine rpm

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)
57.15 (42.62)	1722	3.60 (13.65)	0.444 (0.270)	15.85 (3.12)
42.40 (31.62)	1721	2.68 (10.16)	0.445 (0.271)	15.79 (3.11)
28.60 (21.33)	1731	2.01 (7.59)	0.493 (0.300)	14.26 (2.81)
14.30 (10.66)	1725	1.37 (5.17)	0.672 (0.409)	10.47 (2.06)
0.50 (0.37)	1717	0.82 (3.11)	11.550 (7.031)	0.61 (0.12)

### Normal mode

540 PTO rpm @ 2385 engine rpm

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)
57.40 (42.80)	2399	4.31 (16.33)	0.529 (0.322)	13.30 (2.62)
43.05 (32.10)	2397	3.51 (13.30)	0.574 (0.349)	12.26 (2.41)
28.75 (21.44)	2398	2.75 (10.39)	0.672 (0.409)	10.47 (2.06)
14.20 (10.59)	2401	2.05 (7.76)	1.015 (0.618)	6.93 (1.36)
0.50 (0.37)	2391	1.41 (5.34)	19.830 (12.071)	0.35 (0.07)



**John Deere 5093E Ltd Diesel**  
 Institute of Agriculture and Natural Resources  
 University of Nebraska-Lincoln