

# SUMMARY OF OECD TEST 2792-NEBRASKA SUMMARY 918

## MASSEY FERGUSON 6616 DYNA VT DIESEL

### CONTINUOUSLY VARIABLE TRANSMISSION

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Diesel Consumption		D.E.F. Consumption		Mean Atmospheric Conditions
		Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Gal/hr (l/h)	
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>						
<b>Rated Engine Speed—(PTO speed—1080 rpm)</b>						
127.5 (95.1)	2200	7.55 (28.59)	0.413 (0.251)	16.88 (3.33)	0.32 (1.23)	
<b>Standard Power Take-off Speed (1000 rpm)</b>						
137.7 (102.7)	2037	7.83 (29.64)	0.396 (0.241)	17.58 (3.46)	0.33 (1.26)	
<b>Maximum Power (1 hour)</b>						
140.7 (104.9)	2000	7.94 (30.06)	0.394 (0.240)	17.72 (3.49)	0.34 (1.28)	

#### VARYING POWER AND FUEL CONSUMPTION

127.5 (95.1)	2200	7.55 (28.59)	0.413 (0.251)	16.88 (3.33)	0.32 (1.23)	Air temperature
109.3 (81.5)	2220	6.83 (25.84)	0.436 (0.265)	16.00 (3.15)	0.23 (0.88)	73°F (23°C)
82.5 (61.5)	2231	5.53 (20.92)	0.468 (0.285)	14.91 (2.94)	0.19 (0.71)	Relative humidity
55.1 (41.1)	2242	4.17 (15.79)	0.528 (0.321)	13.21 (2.60)	0.13 (0.51)	68%
27.8 (20.7)	2252	2.96 (11.20)	0.743 (0.452)	9.39 (1.85)	---	Barometer
---	2253	1.79 (6.77)	---	---	---	30.2" Hg (102.3 kPa)

Maximum torque - 454 lb.-ft. (615 Nm) at 1400 rpm  
 Maximum torque rise - 49.0%  
 Torque rise at 1800 engine rpm - 32%  
 Power increase at 2000 engine rpm - 10%

#### DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption		Temp. °F (°C)		Barom. inch Hg (kPa)
					lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	cool- ing med	Air dry bulb	
<b>Maximum Power—Turtle 8</b>									
98.7 (73.6)	7060 (31.4)	5.24 (8.44)	2198	3.3	0.511 (0.311)	13.55 (2.67)	187 (86)	68 (20)	30.1 (101.9)
<b>75% of Pull at Maximum Power—Turtle 8</b>									
71.9 (53.6)	5295 (23.6)	5.09 (8.19)	2212	2.5	0.557 (0.339)	12.40 (2.44)	185 (85)	68 (20)	30.1 (101.9)
<b>50% of Pull at Maximum Power—Turtle 8</b>									
47.2 (35.2)	3420 (15.2)	5.18 (8.33)	2242	1.6	0.709 (0.431)	9.76 (1.92)	185 (85)	70 (21)	30.1 (101.9)
<b>75% of Pull at Reduced Engine Speed—Turtle 12</b>									
70.8 (52.8)	5215 (23.2)	5.09 (8.19)	1472	2.6	0.497 (0.303)	13.91 (2.74)	189 (87)	72 (22)	30.1 (101.9)
<b>50% of Pull at Reduced Engine Speed—Turtle 12</b>									
47.9 (35.7)	3450 (15.3)	5.20 (8.37)	1476	1.4	0.536 (0.326)	12.89 (2.54)	185 (85)	72 (22)	30.1 (101.9)

**Location of tests:** IRSTE A, Centre d'Antony, 1 rue Pierre-Gilles de Gennes CS 10030, Antony, France 92761

**Dates of tests:** July to September, 2013

**Manufacturer:** AGCO S.A. BP 307, Avenue Blaise Pascal, 60026 Beauvais, France

**CONSUMABLE Fluids and OIL: Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.838 Fuel weight 6.98 lbs/gal (0.836 kg/l) Diesel Exhaust Fluid (DEF) 32% aqueous urea solution DEF weight 9.08 lbs/gal (1.091 kg/l) Oil SAE 15W40 API service classification CJ-4 Transmission and hydraulic lubricant BP Terrac Tractan 9 10W/40 Front axle lubricant SAE 85W140 API GL-5**

**ENGINE: Make** AGCO Power Diesel **Type** four cylinder vertical with turbocharger, air to air intercooler and SCR (selective catalyst reduction) exhaust treatment **Serial No.** X00325 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.252" x 5.276" (108.0 mm x 134.0 mm) **Compression ratio** 17.8 to 1 **Displacement** 299 cu in (4910 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** two paper cartridges **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

**CHASSIS: Type** front wheel assist **Serial No.** C 123 901 **Tread width** rear 52.8" (1340 mm) to 87.8" (2230 mm) front 52.8" (1340 mm) to 87.8" (2230 mm) **Wheelbase** 105.1" (2670 mm) **Hydraulic control system** direct engine drive **Transmission** CVT. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. **Nominal travel speeds mph (km/h)** forward: Low range 0-18 (0-30), high range 0-25 (0-40) reverse: Low range 0-11 (0-17), high range 0-18 (0-30) **Clutch** a foot pedal controls the hydrostatic oil flow **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2063 engine rpm or 1000 rpm at 2035 engine rpm **Unladen tractor mass** 15765 lb (7150 kg)

## DRAWBAR PERFORMANCE

### (Unballasted - Front Drive Engaged) MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. <sup>o</sup> F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)	
83.5 (62.3)	14005 (62.3)	2.24 (3.60)	2188	14.2	Turtle 3.5 0.573 (0.349)		12.07 (2.38)	181 (83)	64 (18)	30.1 (101.9)
101.0 (75.3)	12410 (55.2)	3.05 (4.91)	2026	8.3	Turtle 4.5 0.524 (0.319)		13.20 (2.60)	185 (85)	64 (18)	30.1 (101.9)
107.5 (80.2)	9485 (42.2)	4.25 (6.84)	2020	5.8	Turtle 6.5 0.492 (0.299)		14.06 (2.77)	185 (85)	66 (19)	30.1 (101.9)
109.3 (81.5)	8405 (37.4)	4.88 (7.85)	2018	3.5	Turtle 8 0.490 (0.298)		14.11 (2.78)	189 (87)	68 (20)	30.1 (101.9)
108.2 (80.7)	6045 (26.9)	6.71 (10.80)	1995	3.0	Turtle 10 0.506 (0.308)		13.65 (2.69)	189 (87)	72 (22)	30.1 (101.9)
106.6 (79.5)	5060 (22.5)	7.90 (12.71)	2023	2.5	Turtle 12 0.514 (0.312)		13.47 (2.65)	189 (87)	72 (22)	30.1 (101.9)
101.8 (75.9)	4450 (19.8)	8.58 (13.81)	2002	2.1	Turtle 14 0.529 (0.322)		13.06 (2.57)	189 (87)	73 (23)	30.1 (101.9)
107.1 (79.9)	6890 (30.7)	5.83 (9.38)	2017	3.4	Rabbit 9 0.518 (0.315)		13.35 (2.63)	185 (85)	75 (24)	30.1 (101.9)
106.3 (79.3)	5240 (23.3)	7.61 (12.24)	2009	2.8	Rabbit 12 0.518 (0.315)		13.35 (2.63)	187 (86)	75 (24)	30.1 (101.9)
104.9 (78.2)	4475 (19.9)	8.79 (14.14)	1998	2.2	Rabbit 15 0.524 (0.319)		13.20 (2.60)	189 (87)	75 (24)	30.1 (101.9)
101.4 (75.7)	3720 (16.5)	10.22 (16.45)	2024	1.8	Rabbit 17 0.538 (0.327)		12.85 (2.53)	189 (87)	75 (24)	30.1 (101.9)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments.

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The manufacturer's remote hydraulic flow claims of 15 GPM (standard flow) and 26 GPM (combined flow) were not verified. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2792**, Nebraska Summary 918, January 21, 2014.

Roger M. Hoy  
Director

M.F. Kocher  
J.D. Luck  
P.J. Jasa  
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front wheel drive	
	Engaged dB(A)	Disengaged dB(A)
At no load in Turtle 8	71.0	71.0
Bystander		--

#### TIRES, BALLAST AND WEIGHT

**Rear Tires** - No., size, ply & psi(kPa)  
**Front Tires** - No., size, ply & psi(kPa)  
**Height of Drawbar**  
**Static Weight with operator** - Rear  
- Front  
- Total

#### Tested without ballast

Two 580/70R38; \*\*; 14(100)  
Two 480/70R28; \*\*; 14(100)  
21.7 in (550 mm)  
9295 lb (4215 kg)  
6635 lb (3010 kg)  
15930 lb (7225 kg)

## HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: No

OECD Static test

Maximum force exerted through whole range: 11755 lbs (52.3 kN)

**two outlet sets combined**

i) Sustained pressure at compensator cutoff: 2930 psi (202 bar)

ii) Pump delivery rate at minimum pressure: 31.3 GPM (118.5 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 29.1 GPM (110.2 l/min)

Delivery pressure: 2320 psi (160 bar)

Power: 39.4 HP (29.4 kW)

**single outlet set**

i) Sustained pressure at compensator cutoff: 2930 psi (202 bar)

ii) Pump delivery rate at minimum pressure: 31.4 GPM (118.7 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 28.1 GPM (106.2 l/min)

Delivery pressure: 1930 psi (133 bar)

Power: 31.6 HP (23.6 kW)

### HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	31.3	796
B	13.4	340
C	13.9	354
D	11.9	303
E	8.8	223
F	10.3	261
G	34.5	875
H	2.4	60
I	15.2	386
J	24.2	614
K	26.1	662
L	45.6	1157
M	26.1	662
N	39.8	1012
O	7.9	201
P	48.2	1224
Q	34.8	884
R	29.9	760

