

# SUMMARY OF OECD TESTS 1874 & 1878—NEBRASKA SUMMARY 305A

## CHALLENGER MT 545 DIESEL

### 32 SPEED

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed—(PTO speed—1098 rpm)</b>					
120.5 (89.8)	2196	7.45 (28.19)	0.437 (0.266)	16.18 (3.20)	
<b>Standard Power Take-off Speed(1000 rpm)</b>					
126.2 (94.1)	2000	7.21 (27.30)	0.406 (0.247)	17.51 (3.45)	
<b>VARYING POWER AND FUEL CONSUMPTION</b>					
120.5 (89.8)	2196	7.45 (28.19)	0.437 (0.266)	16.18 (3.20)	Air temperature
105.7 (78.8)	2258	7.02 (26.58)	0.472 (0.287)	15.05 (2.97)	72°F(22°C)
80.1 (59.7)	2279	5.95 (22.51)	0.528 (0.321)	13.45 (2.65)	Relative humidity
53.9 (40.2)	2293	4.78 (18.11)	0.631 (0.384)	11.27 (2.22)	64%
26.9 (20.0)	2303	3.60 (13.61)	0.950 (0.578)	7.48 (1.47)	Barometer
--	2322	1.99 (7.54)	--	--	29.7" Hg(100.6 kPa)

Maximum Torque - 370.0 lb.-ft. (501.7 Nm) at 1450 rpm  
 Maximum Torque Rise - 28.4%  
 Torque rise at 1800 engine rpm - 25%

#### DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged)

##### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—13th(4TB) Gear</b>									
113.6 (84.7)	9600 (42.7)	4.44 (7.15)	2202	8	0.484 (0.294)	14.67 (2.89)	187 (86)	61 (16)	30.2 (102.1)
<b>75% of Pull at Maximum Power—13th(4TB) Gear</b>									
91.2 (68.0)	7185 (32.0)	4.76 (7.66)	2274	5	0.518 (0.315)	13.71 (2.70)	192 (89)	57 (14)	29.7 (100.7)
<b>50% of Pull at Maximum Power—13th(4TB) Gear</b>									
63.6 (47.4)	4845 (21.5)	4.92 (7.92)	2293	2	0.593 (0.360)	11.98 (2.36)	190 (88)	57 (14)	29.7 (100.7)
<b>75% of Pull at Reduced Engine Speed—16th(4TC) Gear</b>									
91.7 (68.4)	7195 (32.0)	4.78 (7.69)	1933	5	0.460 (0.280)	15.43 (3.04)	185 (85)	57 (14)	29.7 (100.7)
<b>50% of Pull at Reduced Engine Speed—16th(4TC) Gear</b>									
63.3 (47.2)	4840 (21.5)	4.90 (7.89)	1940	3	0.532 (0.324)	13.35 (2.63)	185 (85)	57 (14)	29.7 (100.7)

**Location of Test:** Groupement d'Antony, Parc de Touvoie, BP 44 Antony, France 92163

**Dates of Test:** October - November, 1999

**Manufacturer:** AGCO S.A. Z.A.-No.2 BP 60307, Avenue Blaise Pascal, 60026 Beauvais, France

**FUEL and OIL:** Fuel No. 2 Diesel **Specific gravity converted to 60°/60° F (15°/15°C)** 0.853  
**Fuel weight** 7.10 lbs/gal (0.851 kg/l) **Oil SAE** 10W30 **API service classification** CD/CE  
**Transmission and hydraulic lubricant** BP Terrac Extra 10W/40 **Front axle lubricant** API GL5 - SAE 85W140

**ENGINE: Make** Perkins Diesel **Type** six cylinder vertical with turbocharger **Serial No.** U668226C **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 3.937" x 5.00" (100.0 mm x 127.0 mm) **Compression ratio** 16.0 to 1 **Displacement** 365 cu in (5985 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

**CHASSIS: Type** 2WD and FWA **Serial No.** G140015 **Tread width** rear 66.9" (1699 mm) to 86.6" (2199 mm) front 2WD - 54.3" (1380 mm) to 91.7" (2330 mm), FWA - 61.7" (1566 mm) to 80.9" (2054 mm) **Wheelbase** 106.3" (2699 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with partial (4) range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.32 (2.13) second 1.55 (2.50) third 1.83 (2.95) fourth 2.14 (3.45) fifth 2.25 (3.62) sixth 2.63 (4.24) seventh 2.96 (4.77) eighth 3.11 (5.01) ninth 3.47 (5.58) tenth 3.64 (5.86) eleventh 4.01 (6.45) twelfth 4.09 (6.59) thirteenth 4.69 (7.55) fourteenth 4.79 (7.71) fifteenth 4.96 (7.99) sixteenth 5.54 (8.92) seventeenth 5.82 (9.36) eighteenth 6.49 (10.44) nineteenth 6.86 (11.04) twentieth 8.03 (12.92) twenty-first 8.44 (13.58) twenty-second 9.88 (15.90) twenty-third 11.11 (17.88) twenty-fourth 11.66 (18.76) twenty-fifth 13.00 (20.92) twenty-sixth 13.65 (21.96) twenty-seventh 15.03 (24.19) twenty-eighth 15.35 (24.70) twenty-ninth 17.59 (28.31) thirtieth 17.96 (28.91) thirty-first 20.77 (33.42) thirty-second 24.31 (39.12) reverse 1.21 (1.94), 1.41 (2.27), 1.67 (2.68), 1.95 (3.14), 2.05 (3.30), 2.40 (3.86), 2.70 (4.34), 2.83 (4.56), 3.16 (5.08), 3.32 (5.34), 3.65 (5.88), 3.73 (6.00), 4.28 (6.88), 4.36 (7.02), 4.52 (7.28), 5.05 (8.12), 5.29 (8.52), 5.91 (9.51), 6.25 (10.06), 7.31 (11.77), 7.69 (12.37), 9.00 (14.48), 10.12 (16.28)

## DRAWBAR PERFORMANCE

### (Unballasted - Front Drive Engaged) MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
11th(4TA) Gear									
106.1 (79.1)	10925 (48.6)	3.64 (5.86)	2212	13	0.507 (0.309)	13.99 (2.76)	189 (87)	61 (16)	30.2 (102.1)
12th(3TC) Gear									
106.6 (79.5)	10845 (48.2)	3.69 (5.93)	2198	13	0.511 (0.311)	13.91 (2.74)	190 (88)	61 (16)	30.2 (102.1)
13th(4TB) Gear									
115.9 (86.4)	10105 (45.0)	4.30 (6.92)	2153	9	0.476 (0.289)	14.92 (2.94)	190 (88)	61 (16)	30.2 (102.1)
14th(3TD) Gear									
116.1 (86.6)	9890 (44.0)	4.40 (7.08)	2151	9	0.477 (0.290)	14.87 (2.93)	190 (88)	61 (16)	30.2 (102.1)
15th(1LA) Gear									
118.1 (88.1)	9575 (42.6)	4.63 (7.45)	2144	7	0.460 (0.280)	15.43 (3.04)	187 (86)	61 (16)	30.2 (102.1)
16th(4TC) Gear									
115.7 (86.3)	8410 (37.4)	5.16 (8.31)	2114	6	0.474 (0.288)	14.97 (2.95)	187 (86)	61 (16)	30.2 (102.1)
17th(1LB) Gear									
118.7 (88.5)	8465 (37.7)	5.26 (8.46)	2060	6	0.450 (0.274)	15.76 (3.11)	189 (87)	61 (16)	30.2 (102.1)
18th(4TD) Gear									
115.9 (86.4)	7215 (32.1)	6.02 (9.68)	2079	5	0.463 (0.281)	15.35 (3.02)	190 (88)	61 (16)	30.2 (102.1)
19th(1LC) Gear									
117.5 (87.6)	6865 (30.5)	6.42 (10.33)	2089	5	0.467 (0.284)	15.23 (3.00)	190 (88)	61 (16)	30.2 (102.1)
20th(1LD) Gear									
116.5 (86.9)	5875 (26.1)	7.43 (11.96)	2048	5	0.460 (0.280)	15.53 (3.04)	189 (87)	61 (16)	30.2 (102.1)
21st(2LA) Gear									
117.6 (87.7)	5775 (25.7)	7.64 (12.29)	2003	5	0.450 (0.274)	15.79 (3.11)	190 (88)	61 (16)	30.2 (102.1)
22nd(2LB) Gear									
115.5 (86.1)	4945 (22.0)	8.76 (14.10)	1992	5	0.453 (0.275)	15.68 (3.09)	189 (87)	61 (16)	30.2 (102.1)

10.62 (17.09), 11.84 (19.06), 12.43 (20.00), 13.69 (22.03), 13.98 (22.49), 16.03 (25.79), 16.36 (26.33), 18.92 (30.44), 22.14 (35.63) **Clutch** multiple wet disc operated by foot pedal **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1976 engine rpm or 1000 rpm at 2000 engine rpm **Unladen tractor mass** 2WD -10460 lb (4745 kg), FWA -11395 lb (5170 kg)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

**NOTE:** The data on this summary was obtained from OECD reports 1874 & 1878 conducted on the Massey Ferguson 6290 Diesel(2WD & FWA).

**Report reissued:** Supplemental sales permit for Challenger MT 545 Diesel, July 2003.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **1874 & 1878**, Nebraska Summary 305A, June 23, 2003.

Leonard L. Bashford  
Director

M.F. Kocher  
W.P. Campbell  
G.J. Hoffman  
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	2WD dB(A)	Engaged dB(A)
At no load in 13th (3TB) gear	78.0	78.0
Bystander	--	--

#### Tested Without Ballast

TIRES AND WEIGHT	Front Wheel Assist	2WD
<b>Rear tires</b> - No., size, ply & psi(kPa)	Two 20.8R38; **,15 (100)	Two 20.8R38; **,15 (100)
<b>Front tires</b> - No., size, ply & psi(kPa)	Two 16.9R28; **,16 (110)	Two 11.00-16; 8; 36 (250)
<b>Height of Drawbar</b>	25.2 in (640 mm)	33.5 in (850 mm)
<b>Static Weight with operator</b> - Rear	6945 lb (3150 kg)	6845 lb (3105 kg)
- Front	4620 lb (2095 kg)	3780 lb (1715 kg)
- Total	11565 lb (5245 kg)	10625 lb (4820 kg)

## DRAWBAR PERFORMANCE

(Unballasted - 2WD)

### FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Fuel Consumption Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
<b>Maximum Power—21st(2LA) Gear</b>									
112.4 (83.8)	5105 (22.7)	8.26 (13.30)	2201	5	0.487 (0.297)	14.57 (2.87)	190 (88)	63 (17)	30.3 (102.5)
<b>75% of Pull at Maximum Power—21st(2LA) Gear</b>									
87.8 (65.5)	3800 (16.9)	8.66 (13.93)	2273	3	0.542 (0.330)	13.10 (2.58)	190 (88)	64 (18)	30.2 (102.1)
<b>50% of Pull at Maximum Power—21st(2LA) Gear</b>									
59.9 (44.7)	2540 (11.3)	8.85 (14.24)	2294	2	0.643 (0.391)	11.04 (2.18)	189 (87)	64 (18)	30.2 (102.1)
<b>75% of Pull at Reduced Engine Speed—22nd(2LB) Gear</b>									
87.5 (65.2)	3815 (17.0)	8.60 (13.84)	1927	3	0.471 (0.286)	15.09 (2.97)	187 (86)	64 (18)	30.2 (102.1)
<b>50% of Pull at Reduced Engine Speed—22nd(2LB) Gear</b>									
60.3 (45.0)	2555 (11.4)	8.86 (14.26)	1959	2	0.548 (0.333)	12.96 (2.55)	187 (86)	64 (18)	30.2 (102.1)

### MAXIMUM POWER IN SELECTED GEARS

10th(2TD) Gear									
80.7 (60.2)	9210 (41.0)	3.29 (5.29)	2271	15	0.595 (0.362)	11.93 (2.35)	190 (88)	63 (17)	30.3 (102.5)
11th(4TA) Gear									
89.2 (66.5)	9195 (40.9)	3.64 (5.85)	2254	14	0.560 (0.341)	12.68 (2.50)	190 (88)	63 (17)	30.3 (102.5)
12th(3TC) Gear									
93.1 (69.4)	9195 (40.9)	3.80 (6.11)	2251	12	0.549 (0.334)	12.94 (2.55)	190 (88)	63 (17)	30.3 (102.5)
13th(4TB) Gear									
103.8 (77.4)	9155 (40.7)	4.26 (6.85)	2218	12	0.516 (0.314)	13.76 (2.71)	189 (87)	63 (17)	30.3 (102.5)
14th(3TD) Gear									
106.9 (79.7)	9210 (41.0)	4.35 (7.00)	2200	12	0.507 (0.309)	13.99 (2.76)	189 (87)	63 (17)	30.3 (102.5)
15th(1LA) Gear									
108.4 (80.8)	9015 (40.1)	4.51 (7.25)	2183	11	0.507 (0.309)	13.99 (2.76)	189 (87)	63 (17)	30.3 (102.5)
16th(4TC) Gear									
112.6 (84.0)	8230 (36.6)	5.13 (8.26)	2169	9	0.492 (0.299)	14.43 (2.84)	189 (87)	63 (17)	30.3 (102.5)
17th(1LB) Gear									
114.5 (85.4)	8245 (36.7)	5.21 (8.38)	2110	9	0.479 (0.291)	14.82 (2.92)	190 (88)	63 (17)	30.3 (102.5)
18th(4TD) Gear									
115.8 (86.4)	7445 (33.1)	5.83 (9.39)	2088	9	0.469 (0.286)	15.13 (2.98)	190 (88)	63 (17)	30.3 (102.5)
19th(1LC) Gear									
114.9 (85.7)	6945 (30.9)	6.20 (9.97)	2088	8	0.472 (0.287)	15.04 (2.96)	190 (88)	63 (17)	30.3 (102.5)
20th(1LD) Gear									
117.1 (87.3)	6140 (27.3)	7.15 (11.51)	2032	7	0.455 (0.277)	15.58 (3.07)	190 (88)	63 (17)	30.3 (102.5)
21st(2LA) Gear									
117.3 (87.5)	5775 (25.7)	7.62 (12.27)	2048	6	0.455 (0.277)	15.58 (3.07)	190 (88)	63 (17)	30.3 (102.5)
22nd(2LB) Gear									
116.5 (86.9)	4945 (22.0)	8.84 (14.22)	2010	5	0.451 (0.275)	15.74 (3.10)	190 (88)	63 (17)	30.3 (102.5)

### THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum Force Exerted

Through Whole Range: 9414 lbs (41.9 kN)

- i) Opening pressure of relief valve: NA
- Sustained pressure of the open relief valve: 2890 psi (199 bar)
- ii) Pump delivery rate at minimum pressure and rated engine speed: 28.6 GPM (108.3 l/min)
- iii) Pump delivery rate at maximum hydraulic power: 24.6 GPM (93.1 l/min)
- Delivery pressure: 2750 psi (190 bar)
- Power: 39.5 HP (29.4 kW)

### THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi. (bar) 2850 (196)  
 Location: lift cylinder  
 Hydraulic oil temperature: °F (°C) 149 (65)  
 Location: hydraulic sump  
 Category: II  
 Quick attach: none

#### SAE Static Test—System pressure 2558 psi (176 Bar)

Hitch point distance to ground level in. (mm)	7.9 (201)	14.9 (378)	21.9 (556)	28.9 (734)	35.9 (912)
Lift force on frame lb	13338	12708	12222	11412	10431
" " " " " (kN)	(59.3)	(56.5)	(54.4)	(52.3)	(46.4)

#### HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	26.9	683
B	11.6	295
C	13.9	354
D	13.0	330
E	7.9	200
F	10.2	260
G	32.3	820
H	1.7	43
I	15.0	382
J	22.1	560
K	21.7	550
L	40.9	1040
M	23.2	590
N	37.0	940
O	7.9	200
P	46.1	1170
Q	36.1	918
R	28.3	719

