

SUMMARY OF OECD TEST 2753-NEBRASKA SUMMARY 905 CHALLENGER MT525D AUTOPOWER IV DIESEL 16 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Diesel Consumption		D.E.F. Consumption		Mean Atmospheric Conditions
		Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Gal/hr (l/h)	
MAXIMUM POWER AND FUEL CONSUMPTION						
Rated Engine Speed—(PTO speed—1035 rpm)						
127.1 (94.8)	2101	7.55 (28.58)	0.413 (0.252)	16.85 (3.32)	0.31 (1.18)	
Standard Power Take-off Speed (1000 rpm)						
137.7 (102.7)	2030	7.93 (30.01)	0.401 (0.244)	17.36 (3.42)	0.35 (1.34)	
Maximum Power (1 hour)						
141.9 (105.8)	2000	8.05 (30.47)	0.396 (0.241)	17.61 (3.47)	0.34 (1.31)	

VARYING POWER AND FUEL CONSUMPTION

127.1 (94.8)	2101	7.55 (28.58)	0.413 (0.252)	16.85 (3.32)	0.31 (1.18)	Air temperature
108.8 (81.1)	2118	6.69 (25.33)	0.430 (0.261)	16.22 (3.20)	0.30 (1.12)	68°F (20°C)
81.7 (60.9)	2127	5.46 (20.66)	0.465 (0.283)	14.97 (2.95)	0.22 (0.85)	Relative humidity
55.3 (41.2)	2137	4.23 (16.02)	0.534 (0.325)	13.05 (2.57)	0.17 (0.64)	45%
27.6 (20.6)	2146	3.05 (11.54)	0.769 (0.468)	9.06 (1.79)	0.12 (0.46)	Barometer
--	2155	1.99 (7.53)	--	--	--	29.9" Hg (101.1 kPa)

Maximum torque - 458.1 lb.-ft. (621.1 Nm) at 1200 rpm
 Maximum torque rise - 44.1%
 Torque rise at 1700 engine rpm - 30%
 Power increase at 2000 engine rpm - 11.6%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—9th(3A) Gear									
106.6 (79.5)	6875 (30.6)	5.82 (9.36)	2096	4.7	0.461 (0.280)	15.08 (2.97)	181 (83)	59 (15)	29.8 (101.0)
75% of Pull at Maximum Power—9th(3A) Gear									
81.8 (61.0)	5170 (23.0)	5.93 (9.55)	2130	4.2	0.498 (0.303)	13.96 (2.75)	180 (82)	59 (15)	29.8 (101.0)
50% of Pull at Maximum Power—9th(3A) Gear									
54.8 (40.9)	3400 (15.1)	6.05 (9.73)	2137	2.3	0.598 (0.364)	11.62 (2.29)	178 (81)	59 (15)	29.8 (101.0)
75% of Pull at Reduced Engine Speed—10th(3B) Gear									
81.8 (61.0)	5205 (23.1)	5.90 (9.49)	1703	4.1	0.445 (0.271)	15.63 (3.08)	178 (81)	59 (15)	29.8 (101.0)
50% of Pull at Reduced Engine Speed—10th(3B) Gear									
55.5 (41.4)	3430 (15.2)	6.07 (9.77)	1732	2.4	0.496 (0.302)	14.01 (2.76)	178 (81)	59 (15)	29.8 (101.0)

Location of tests: IRSTEА, Centre d'Antony, 1 rue Pierre-Gilles de Gennes CS 10030 Antony, 92163, Cedex, France

Dates of tests: April - May, 2012

Manufacturer: AGCO S.A. BP 307, Avenue Blaise Pascal, 60026 Beauvais, France

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.837 **Fuel weight** 6.97 lbs/gal (0.835 kg/l) **Diesel Exhaust Fluid (DEF)** 32% aqueous urea solution **DEF weight** 9.10 lbs/gal (1.091 kg/l) **Oil SAE** 15W40 **API service classification** CJ-4 **Transmission and hydraulic lubricant** BP Terrac Tractan 9 15W/40 **Front axle lubricant** BP Terrac Tractan 9 15W/40

ENGINE: Make Sisu AGCO Power Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler and SCR (selective catalyst reduction) exhaust treatment **Serial No.** W00406 **Crankshaft** lengthwise **Rated engine speed** 2100 **Bore and stroke** 4.252" x 4.724" (108.0 mm x 120.0 mm) **Compression ratio** 17.4 to 1 **Displacement** 402 cu in (6596 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** two paper cartridges **Muffler** vertical **Cooling medium** **temperature control** thermostat and variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.** B 230 901 **Tread width** rear 52.8" (1340 mm) to 87.8" (2230 mm) front 52.8" (1340 mm) to 87.8" (2230 mm) **Wheelbase** 113.2" (2875 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with partial (4) range operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.24 (2.00) second 1.53 (2.46) third 1.86 (3.00) fourth 2.29 (3.69) fifth 2.95 (4.74) sixth 3.62 (5.83) seventh 4.42 (7.11) eighth 5.43 (8.74) ninth 5.98 (9.62) tenth 7.36 (11.84) eleventh 8.97 (14.44) twelfth 11.04 (17.76) thirteenth 13.79 (22.20) fourteenth 16.96 (27.30) fifteenth 20.69 (33.30) sixteenth 25.46 (40.97) reverse 1.24 (2.00), 1.53 (2.46), 1.86 (3.00), 2.29 (3.69), 2.95 (4.74), 3.62 (5.83), 4.42 (7.11), 5.43 (8.74), 5.98 (9.62), 7.36 (11.84), 8.97 (14.44), 11.04 (17.76), 13.79 (22.20), 16.96 (27.30), 20.69 (33.30), 25.46 (40.97)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
5th(2A) Gear									
87.6 (65.3)	12295 (54.7)	2.67 (4.30)	2118	13.5	0.529 (0.322)	13.15 (2.59)	178 (81)	55 (13)	30.1 (102.0)
6th(2B) Gear									
103.8 (77.4)	12005 (53.4)	3.24 (5.22)	2064	12.2	0.478 (0.291)	14.52 (2.86)	180 (82)	57 (14)	29.8 (101.0)
7th(2C) Gear									
112.0 (83.5)	10705 (47.6)	3.92 (6.32)	1998	9.2	0.459 (0.279)	15.18 (2.99)	183 (84)	57 (14)	29.8 (101.0)
8th(2D) Gear									
116.0 (86.5)	8755 (38.9)	4.97 (7.99)	2003	6.0	0.445 (0.271)	15.63 (3.08)	180 (82)	57 (14)	29.8 (101.0)
9th(3A) Gear									
118.1 (88.1)	8070 (35.9)	5.49 (8.83)	2001	5.2	0.444 (0.270)	15.68 (3.09)	181 (83)	59 (15)	29.8 (101.0)
10th(3B) Gear									
118.2 (88.1)	6430 (28.6)	6.89 (11.08)	2005	4.5	0.446 (0.272)	15.57 (3.07)	183 (84)	59 (15)	29.8 (101.0)
11th(3C) Gear									
116.7 (87.0)	5150 (22.9)	8.50 (13.68)	2002	3.5	0.449 (0.273)	15.48 (3.05)	183 (84)	57 (14)	29.8 (101.0)
12th(3D) Gear									
113.3 (84.5)	4100 (18.3)	10.36 (16.67)	1990	3.0	0.464 (0.282)	14.97 (2.95)	183 (84)	59 (15)	29.8 (101.0)

Clutch multiple wet disc operated by foot pedal
Brakes multiple wet disc hydraulically operated by two foot pedals that can be locked together
Steering hydrostatic **Power take-off** 540 rpm at 1885 engine rpm or 1000 rpm at 2030 engine rpm **Unladen tractor mass** 13920 lb (6315 kg)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

NOTE: The data on this summary was obtained from OECD report 2753 conducted on the Massey Ferguson 7615 DYNA 4 Diesel.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's power bulge claim of 15 hp nor remote hydraulic flow claims of 29 GPM (110 lpm) with two outlets combined nor 24.3 GPM (92 lpm) single outlet set. The manufacturer's remote hydraulic flow claim of 39 GPM (150 lpm) for optional pump was not verified. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2753**, Nebraska Summary 905, January 22, 2014.

Roger M. Hoy
 Director

M.F. Kocher
 J.D. Luck
 P.J. Jasa
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB

	Front wheel drive	
	Engaged	Disengaged
	dB(A)	dB(A)
At no load in 7th (2C) gear	69.0	69.0
Bystander	--	--

TIRES, BALLAST AND WEIGHT

Rear Tires - No., size, ply & psi(kPa)
Front Tires - No., size, ply & psi(kPa)
Height of Drawbar
Static Weight with operator - Rear
 - Front
 - Total

Tested without ballast

Two 520/85R38; **; 14(100)
 Two 420/85R28; **; 15(105)
 19.7 in (500 mm)
 7780 lb (3530 kg)
 6305 lb (2860 kg)
 14085 lb (6390 kg)


HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: None

OECD Static test

- Maximum force exerted through whole range: 9305 lbs (41.4 kN)
- i) Sustained pressure of the open relief valve: 2780 psi (191 bar)
two outlet sets combined
- ii) Pump delivery rate at minimum pressure: 25.1 GPM (94.9 l/min)
- iii) Pump delivery rate at maximum
hydraulic power: 23.4 GPM (88.9 l/min)
Delivery pressure: 2170 psi (149 bar)
Power: 29.6 HP (22.1 kW)
single outlet set
- ii) Pump delivery rate at minimum pressure: 23.1 GPM (87.6 l/min)
- iii) Pump delivery rate at maximum
hydraulic power: 22.1 GPM (83.6 l/min)
Delivery pressure: 1835 psi (126 bar)
Power: 23.6 HP (17.6 kW)



HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	27.7	704
B	11.6	295
C	13.9	354
D	13.0	330
E	9.8	250
F	11.0	280
G	34.4	875
H	3.2	82
I	16.3	413
J	23.4	595
K	21.4	543
L	43.3	1101
M	24.6	626
N	37.0	940
O	8.3	212
P	47.4	1205
Q	36.6	930
R	30.7	780