

SUMMARY OF OECD TEST 2720-NEBRASKA SUMMARY 874

CHALLENGER MT665D DIESEL

TECHSTAR TRANSMISSION

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Diesel Consumption		D.E.F. Consumption		Mean Atmospheric Conditions
		Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Gal/hr (l/h)	
MAXIMUM POWER AND FUEL CONSUMPTION						
Rated Engine Speed—(PTO speed—1066 rpm)						
262.7 (195.9)	2100	14.56 (55.12)	0.390 (0.237)	18.04 (3.55)	0.83 (3.14)	
Standard Power Take-off Speed (1000 rpm)						
293.1 (218.6)	1970	15.78 (59.73)	0.378 (0.230)	18.57 (3.66)	0.92 (3.49)	
Maximum Power (1 hour)						
298.9 (222.9)	1950	15.93 (60.31)	0.374 (0.228)	18.76 (3.70)	0.94 (3.56)	
VARYING POWER AND FUEL CONSUMPTION						
262.7 (195.9)	2100	14.56 (55.12)	0.390 (0.237)	18.04 (3.55)	0.83 (3.14)	Air temperature
225.4 (168.1)	2120	12.88 (48.74)	0.401 (0.244)	17.50 (3.45)	0.66 (2.51)	72°F (22°C)
169.9 (126.7)	2131	10.08 (38.14)	0.417 (0.253)	16.86 (3.32)	0.54 (2.06)	Relative humidity
113.7 (84.8)	2140	7.48 (28.31)	0.461 (0.281)	15.20 (3.00)	0.38 (1.42)	21%
57.1 (42.6)	2149	5.00 (18.94)	0.615 (0.374)	11.42 (2.25)	0.22 (0.82)	Barometer
----	2157	2.71 (10.27)	----	----	0.00 (0.00)	30.1" Hg (102.0 kPa)

Maximum torque - 965 lb.-ft. (1308 Nm) at 1500 rpm
 Maximum torque rise - 46.9%
 Torque rise at 1700 engine rpm - 35%
 Power increase at 1950 engine rpm - 13.8%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Turtle 9									
219.3 (163.5)	14630 (65.08)	5.62 (9.04)	2101	2.9	0.461 (0.281)	15.07 (2.97)	176 (80)	70 (21)	29.2 (98.9)
75% of Pull at Maximum Power—Turtle 9									
168.7 (125.8)	10950 (48.71)	5.78 (9.30)	2122	2.0	0.482 (0.293)	14.42 (2.84)	174 (79)	72 (22)	29.2 (99.0)
50% of Pull at Maximum Power—Turtle 9									
115.2 (85.9)	7320 (32.55)	5.90 (9.50)	2133	1.2	0.531 (0.323)	13.10 (2.58)	169 (76)	72 (22)	29.0 (98.2)
75% of Pull at Reduced Engine Speed—Turtle 11									
169.1 (126.1)	10940 (48.66)	5.80 (9.33)	1803	2.0	0.448 (0.272)	15.51 (3.05)	165 (74)	70 (21)	29.2 (98.9)
50% of Pull at Reduced Engine Speed—Turtle 11									
114.6 (85.5)	7270 (32.34)	5.91 (9.51)	1810	1.4	0.483 (0.293)	14.39 (2.83)	165 (74)	72 (22)	29.2 (99.0)

Location of tests: DLG - Test Centre, Technology and Farm inputs, Max-Eyth-Weg 1, D-64823 Gross-Umstadt, Germany

Dates of tests: March - May, 2012.

Manufacturer: AGCO S.A. ZA, n2, BP 60307, Avenue Blaise Pascal, 60026 Beauvais, Cedex, France

CONSUMABLE FLUIDS: Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.843 Fuel weight 7.04 lbs/gal (0.842 kg/l) Diesel Exhaust Fluid (DEF) 32% aqueous urea solution DEF weight 9.10 lbs/gal (1.093 kg/l) Oil SAE 10W40 API service classification CI4 Transmission and hydraulic lubricant BP STOU 10W/40 Front axle lubricant SAE 85W90 API GL5

ENGINE: Make Sisu Diesel Type six cylinder vertical with turbocharger, air to air intercooler and D.E.F (diesel exhaust fluid) technology Serial No. W423 Crankshaft lengthwise Rated engine speed 2100 Bore and stroke 4.370" x 5.709" (111.0 mm x 145.0 mm) Compression ratio 16.7 to 1 Displacement 513 cu in (8419 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil Fuel filter one paper element Muffler vertical Cooling medium temperature control thermostat and variable speed fan

CHASSIS: Type front wheel assist Serial No. V319022 Tread width rear 72.8" (1850 mm) to 74.8" (1900 mm) front 70.9" (1800 mm) to 76.8" (1950 mm) Wheelbase 122.2" (3105 mm) Hydraulic control system direct engine drive Transmission CVT. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. Nominal travel speeds mph (km/h) forward: Low range 0-18 (0-30), high range 0-25 (0-40) reverse: Low range 0-12 (0-19), high range 0-12 (0-39) Clutch a foot pedal controls the hydrostatic oil flow Brakes multiple wet disc hydraulically operated by two foot pedals that can be locked together Steering hydrostatic Power take-off 1000 rpm at 1970 engine rpm Unladen tractor mass 25200 lb (11430 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER AT SELECTED SPEEDS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. ^o F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Turtle 6									
207.7 (154.9)	24890 (110.72)	3.13 (5.04)	1999	15.0	0.520 (0.316)	13.32 (2.62)	183 (84)	82 (28)	28.9 (97.9)
Turtle 7.5									
245.1 (182.8)	21995 (97.84)	4.18 (6.72)	1949	5.5	0.453 (0.276)	15.35 (3.03)	154 (68)	61 (16)	29.3 (99.1)
Turtle 9									
247.7 (184.7)	18035 (80.23)	5.15 (8.29)	1948	4.0	0.451 (0.275)	15.46 (3.05)	154 (68)	61 (16)	29.3 (99.1)
Turtle 11									
246.5 (183.8)	14965 (66.56)	6.18 (9.94)	1953	3.1	0.449 (0.274)	15.51 (3.06)	158 (70)	61 (16)	29.3 (99.1)
Turtle 13									
244.3 (182.2)	12710 (56.54)	7.21 (11.60)	1949	2.6	0.453 (0.276)	15.36 (3.03)	163 (73)	59 (15)	29.3 (99.1)
Turtle 15									
241.1 (179.8)	10795 (48.03)	8.38 (13.48)	1952	2.1	0.458 (0.280)	15.20 (3.00)	165 (74)	59 (15)	29.2 (99.0)
Turtle 17									
237.5 (177.1)	9235 (41.09)	9.64 (15.52)	1956	1.7	0.462 (0.282)	15.05 (2.97)	178 (81)	59 (15)	29.2 (99.0)
Rabbit 9									
230.5 (171.9)	16680 (74.20)	5.18 (8.34)	1950	3.8	0.481 (0.292)	14.44 (2.84)	163 (73)	79 (26)	28.9 (97.9)
Rabbit 11									
237.8 (177.3)	14220 (63.26)	6.27 (10.09)	1951	3.0	0.468 (0.284)	14.84 (2.92)	185 (85)	75 (24)	28.9 (97.9)
Rabbit 13									
241.1 (179.8)	12170 (54.13)	7.43 (11.96)	1954	2.6	0.459 (0.279)	15.14 (2.98)	178 (81)	75 (24)	28.9 (97.9)
Rabbit 15									
244.2 (182.1)	10660 (47.41)	8.59 (13.82)	1954	2.2	0.454 (0.276)	15.33 (3.02)	181 (83)	59 (15)	29.3 (99.1)
Rabbit 17									
244.3 (182.2)	9360 (41.63)	9.79 (15.76)	1951	1.8	0.454 (0.276)	15.33 (3.02)	174 (79)	59 (15)	29.3 (99.1)
Rabbit 19									
239.4 (178.5)	8225 (36.59)	10.91 (17.56)	1956	1.5	0.460 (0.280)	15.13 (2.98)	170 (77)	61 (16)	29.3 (99.1)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

NOTE: The data on this summary was obtained from OECD report 2720 conducted on the Massey Ferguson 8670 Diesel.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's 3 point lift claim of 22760 lbs (10323 kg). The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2720**, Nebraska Summary 874, January 30, 2013.

Roger M. Hoy
Director

M.R. Riley
P.J. Jasa
J.D. Luck
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	dB(A)
At no load in Turtle - 4.6 mph (7.5 km/h) - no load	71.0
Bystander	---

TIRES AND WEIGHT

Rear Tires - No., size, ply & psi (kPa)
Front Tires - No., size, ply & psi (kPa)
Height of Drawbar
Static Weight with operator - Rear
- Front
- Total

Tested Without Ballast
Two 710/75R42;***;12(80)
Two 600/65R34;***;12(80)
22.2 in (565 mm)
14100 lb (6395 kg)
11265 lb (5110 kg)
25365 lb (11505 kg)

HYDRAULIC PERFORMANCE

CATEGORY: III

Quick Attach: No, Yes

OECD Static test

Maximum force exerted through whole range: 17850 lbs (79.4 kN) (claw type lower links)
20345 lbs (90.5 kN) (Quick hitch)

i) Sustained pressure at compensator cutoff: 2755 psi (190 bar)
two outlet sets combined

ii) Pump delivery rate at minimum pressure: 46.2 GPM (174.9 l/min)

iii) Pump delivery rate at maximum
hydraulic power: 37.9 GPM (143.6 l/min)
Delivery pressure: 2380 psi (164 bar)
Power: 52.6 HP (39.3 kW)

single outlet set

ii) Pump delivery rate at minimum pressure: 28.9 GPM (109.3 l/min)

iii) Pump delivery rate at maximum
hydraulic power: 26.1 GPM (103.2 l/min)
Delivery pressure: 2290 psi (158 bar)
Power: 34.9 HP (27.2 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	Claw lower links		Quick Hitch	
	inch	mm	inch	mm
A	31.9	810	31.9	810
B	14.6	370	14.6	370
C	19.1	484	19.1	484
D	15.9	405	15.9	405
E	12.4	315	12.4	315
F	13.0	330	13.0	330
G	40.4	1025	40.4	1025
H	2.0	50	2.0	50
I	17.7	450	17.7	450
J	27.4	695	27.4	695
K	24.8	630	24.8	630
L	52.4	1330	52.4	1330
*L'	--	--	56.3	1430
M	29.8	757	33.7	857
N	42.9	1090	42.9	1090
O	9.1	230	9.8	250
P	54.3	1380	50.4	1280
Q	41.5	1055	41.2	1046
R	37.0	940	37.0	940

*L' to Quick Attach ends

