

# SUMMARY OF OECD TESTS 1946 and 1947—NEBRASKA SUMMARY 359

## NEW HOLLAND TN 70D DIESEL

### ALSO NEW HOLLAND TN 70S DIESEL

### ALSO NEW HOLLAND TN 70 DIESEL

## 8 SPEED

### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>					
<b>Rated Engine Speed (PTO speed 565 rpm)</b>					
60.1 (44.8)	2300	3.52 (13.31)	0.410 (0.250)	17.08 (3.37)	
<b>Standard Power Take-off speed (540 rpm)</b>					
59.8 (44.6)	2199	3.42 (12.95)	0.401 (0.244)	17.46 (3.44)	
<b>VARYING POWER AND FUEL CONSUMPTION</b>					
60.1 (44.8)	2300	3.52 (13.31)	0.410 (0.250)	17.08 (3.37)	Air temperature
54.3 (40.5)	2431	3.36 (12.73)	0.434 (0.264)	16.14 (3.18)	75°F (24°C)
41.3 (30.8)	2447	2.71 (10.26)	0.460 (0.280)	15.23 (3.00)	Relative humidity
27.8 (20.7)	2492	2.11 (7.99)	0.533 (0.324)	13.15 (2.59)	60%
14.1 (10.5)	2496	1.49 (5.65)	0.746 (0.454)	9.39 (1.85)	Barometer
--	2512	0.96 (3.64)	--	--	28.8" Hg (97.4 kPa)

Maximum Torque -179.2 lb.-ft. (242.9 Nm) at 1413 rpm  
 Maximum Torque Rise -30.6%  
 Torque rise at 1800 engine rpm -19%

### DRAWBAR PERFORMANCE

#### BALLASTED - FRONT DRIVE ENGAGED FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption		Temp. °F (°C)		Barom. inch Hg (kPa)
					lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	cool- ing med	Air dry bulb	
<b>75% of Pull at Maximum Power Five Hours 4th (4S) Gear</b>									
40.5 (30.2)	3170 (14.1)	4.79 (7.71)	2380	3.0	0.508 (0.309)	13.80 (2.72)	178 (81)	39 (4)	29.0 (98.1)
<b>MAXIMUM POWER IN SELECTED GEARS</b>									
<b>2nd (2S) Gear</b>									
38.2 (28.5)	7375 (32.8)	1.94 (3.12)	2360	15.1	0.532 (0.324)	13.18 (2.60)	176 (80)	49 (9)	29.1 (98.5)
<b>3rd (3S) Gear</b>									
50.2 (37.4)	6345 (28.2)	2.96 (4.77)	2300	8.2	0.484 (0.294)	14.48 (2.85)	178 (81)	45 (7)	29.1 (98.5)
<b>4th (4S) Gear</b>									
51.6 (38.5)	4235 (18.8)	4.57 (7.36)	2300	4.3	0.478 (0.291)	14.67 (2.89)	178 (81)	45 (7)	29.1 (98.5)
<b>5th (1F) Gear</b>									
53.3 (39.8)	3560 (15.8)	5.61 (9.02)	2300	2.6	0.460 (0.280)	15.23 (3.00)	176 (80)	43 (6)	29.1 (98.5)
<b>6th (2F) Gear</b>									
43.7 (32.6)	1960 (8.7)	8.36 (13.46)	2300	2.0	0.562 (0.342)	12.48 (2.46)	178 (81)	43 (6)	29.1 (98.5)

**Location of Test:** Istituto Per La Meccanizzazione Agricola (IMA) Strada delle Cacce, 73-10135 Torino, Italy

**Dates of Test:** November - December, 2000

**Manufacturer:** New Holland Italia S.p.A., Viale delle Nazioni, 55-41100, Modena, Italy

**FUEL and OIL :** Fuel No. 2 Diesel **Specific gravity converted to 60°/60° F (15°/15°C)** 0.842 **Fuel weight** 7.01 lbs/gal (0.840 kg/l) **Oil** SAE 15W40 **API service classification** SE/CD **Oil consumption for 10 hours** 0.02 lb (7.5 gm) **Transmission and hydraulic lubricant** SAE 80W90 GL-4 **Front axle lubricant** SAE 80W90 GL-4

**ENGINE: Make** New Holland **Diesel Type** three cylinder vertical with turbocharger **Serial No.** 663654 **Crankshaft** lengthwise **Rated Engine speed** 2300 **Bore and stroke** 4.094" x 4.528" (104.0 mm x 115.0 mm) **Compression ratio** 18 to 1 **Displacement** 179 cu in (2930 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil Cooler** engine coolant heat exchanger for crankcase oil **Fuel filter** one paper element **Muffler** vertical **Cooling medium temperature control** thermostat

**CHASSIS: Type** 2WD and front wheel assist **Serial No.** 001203572 **Tread width** rear 48.1" (1240 mm) to 75.9" (1920 mm) front: 2WD - 53.4" (1357 mm) to 77.0" (1957 mm), FWA - 54.4" (1382 mm) to 71.3" (1812 mm) **Wheel base** 2WD - 83.9" (2130 mm) FWA - 81.3" (2065 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio **Nominal travel speeds mph (km/h)** first 1.47 (2.37) second 2.19 (3.53) third 3.23 (5.19) fourth 4.78 (7.69) fifth 5.77 (9.28) sixth 8.59 (13.83) seventh 12.63 (20.33) eighth 18.72 (30.12) reverse 1.42 (2.29), 2.13 (3.42), 3.13 (5.03), 4.63 (7.45), 5.59 (8.99), 8.33 (13.40), 12.24 (19.69), 18.12 (29.17) **Clutch** dual dry disc operated by foot pedal **Brakes** wet disc hydraulically operated by two foot pedals which can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 2198 engine rpm or 1000 rpm at 2125 engine rpm **Unladen tractor mass** 2WD - 4850 lb (2200 kg), FWA - 5665 lb (2570 kg)

**DRAWBAR PERFORMANCE**  
**BALLASTED - 2WD**  
**FUEL CONSUMPTION CHARACTERISTICS**

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)	
<b>75% of Pull at Maximum Power Five Hours 4th (4S) Gear</b>									
40.0 (29.8)	3175 (14.1)	4.72 (7.59)	2400	3.3	0.510 (0.310)	13.76 (2.71)	174 (79)	41 (5)	29.0 (98.1)
<b>MAXIMUM POWER IN SELECTED GEARS</b>									
3rd (3S) Gear									
43.7 (32.6)	5990 (26.6)	2.73 (4.40)	2350	15.2	0.545 (0.332)	12.84 (2.53)	178 (81)	46 (8)	29.0 (98.2)
4th (4S) Gear									
50.3 (37.5)	4225 (18.8)	4.46 (7.17)	2300	5.1	0.478 (0.291)	14.66 (2.89)	178 (81)	45 (7)	29.0 (98.2)
5th (1F) Gear									
51.1 (38.1)	3535 (15.7)	5.42 (8.73)	2300	4.0	0.479 (0.291)	14.63 (2.88)	178 (81)	43 (6)	29.0 (98.2)
6th (2F) Gear									
46.0 (34.3)	2100 (9.3)	8.22 (13.23)	2300	2.3	0.505 (0.307)	13.87 (2.73)	176 (80)	41 (5)	29.0 (98.2)

**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD test procedures. The performance results on this summary were taken from OECD tests conducted under the Code I Test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **1946** and **1947**, Nebraska Summary 359, November 8, 2001.

Brent T. Sampson  
Test Engineer

L.L. Bashford  
M.F. Kocher  
V.I. Adamchuk  
Board of Tractor Test Engineers

**TN 70D-2WD**

<b>TIRES, BALLAST AND WEIGHT</b>		<b>With Ballast</b>	<b>Without Ballast</b>
<b>Rear Tires</b>	-No., size, ply & psi (kPa)	Two 480/70R30; **,14 (98)	Two 480/70R30; **,14 (98)
<b>Ballast</b>	-Liquid (total)	None	None
	-Cast Iron (total)	440 lb (200 kg)	None
<b>Front Tires</b>	-No., size, ply & psi (kPa)	Two 7.50-16;8;54 (370)	Two 7.50-16;8;54 (370)
<b>Ballast</b>	-Liquid (total)	None	None
	-Cast Iron (total)	685 lb (310 kg)	None
<b>Height of Drawbar</b>		27.4 in (695 mm)	27.6 in (700 mm)
<b>Static Weight with Operator</b>	-Rear	3585 lb (1625 kg)	3140 lb (1425 kg)
	-Front	2555 lb (1160 kg)	1875 lb (850 kg)
	-Total	6140 lb (2785 kg)	5015 lb (2275 kg)

**TN 70D-FWA**

<b>TIRES, BALLAST AND WEIGHT</b>		<b>With Ballast</b>	<b>Without Ballast</b>
<b>Rear Tires</b>	-No., size, ply & psi (kPa)	Two 480/70R30; **,14 (98)	Two 480/70R30; **,14 (98)
<b>Ballast</b>	-Liquid (total)	None	None
	-Cast Iron (total)	440 lb (200 kg)	None
<b>Front Tires</b>	-No., size, ply & psi (kPa)	Two 320/70R24; **,21 (145)	Two 320/70R24; **,21 (145)
<b>Ballast</b>	-Liquid (total)	None	None
	-Cast Iron (total)	685 lb (310 kg)	None
<b>Height of Drawbar</b>		17.9 in (455 mm)	18.1 in (460 mm)
<b>Static Weight with Operator</b>	-Rear	4100 lb (1820 kg)	3570 lb (1620 kg)
	-Front	2945 lb (1335 kg)	2260 lb (1025 kg)
	-Total	6955 lb (3155 kg)	5830 lb (2645 kg)

TRACTOR SOUND LEVEL WITHOUT CAB	FWA dB(A)	2WD dB(A)
At no load in 4th(4S) gear	92.8	91.9
Bystander in 8th(4F) gear	85.0	84.7

#### CENTER OF GRAVITY - 2WD

Horizontal distance forward from centerline of rear wheels	31.5 in (800 mm)
Vertical distance above roadway	30.7 in (780 mm)
Horizontal distance from center of rear wheel tread	0.2 in (5 mm) to the left

#### CENTER OF GRAVITY - FWA

Horizontal distance forward from centerline of rear wheels	31.7 in (805 mm)
Vertical distance above roadway	29.5 in (750 mm)
Horizontal distance from center of rear wheel tread	0.2 in (5 mm) to the left

#### TURNING ON A CONCRETE SURFACE (2WD)

Turning radius with brake applied right 122" (3.10 m) left 124" (3.15 m)	
without brake right 142" (3.60 m) left 146" (3.70 m)	
Turning space radius with brake applied right 126" (3.20 m) left 128" (3.25 m)	
without brake right 140" (3.55 m) left 146" (3.70 m)	

#### TURNING ON A CONCRETE SURFACE (FWA)

Turning radius with brake applied right 140" (3.55 m) left 140" (3.55 m)	
without brake right 163" (4.15 m) left 163" (4.15 m)	
Turning space radius with brake applied right 146" (3.70 m) left 146" (3.70 m)	
without brake right 169" (4.30 m) left 169" (4.30 m)	

### THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: II

Quick Attach: None

Maximum Force Exerted Through Whole Range:

4045 lbs (18.0 kN) (at the frame)  
4405 lbs (19.6 kN) (at lower link ends)

i) Opening pressure of relief valve:	NA	<u>High Flow Option</u>
Sustained pressure with relief valve open:	3020 psi (208 bar)	3020 psi (208 bar)
ii) Pump delivery rate at minimum pressure:	12.8 GPM (48.1 l/min)	17.1 GPM (64.9 l/min)
iii) Pump delivery rate at maximum hydraulic power:	11.3 GPM (42.8 l/min)	14.5 GPM (55.0 l/min)
Delivery pressure:	2540 psi (175 bar)	2410 psi (166 bar)
Power:	16.7 HP (12.5 kW)	20.4 HP (15.2 kW)

### HITCH DIMENSIONS AS TESTED NO LOAD

