

SUMMARY OF OECD TEST 2409—NEBRASKA SUMMARY 624

NEW HOLLAND T7030 DIESEL

19 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1022 rpm)					
139.7 (104.2)	2200	9.45 (35.77)	0.467 (0.284)	14.79 (2.91)	
Standard Power Take-off Speed (1000 rpm)					
141.5 (105.5)	2153	9.35 (35.41)	0.456 (0.277)	15.14 (2.98)	
Maximum Power (1 hour)					
163.2 (121.7)	1800	9.50 (35.95)	0.401 (0.244)	17.18 (3.39)	

VARYING POWER AND FUEL CONSUMPTION

139.7 (104.2)	2200	9.45 (35.77)	0.467 (0.284)	14.79 (2.91)	Air temperature
122.0 (91.0)	2260	8.88 (33.63)	0.502 (0.306)	13.74 (2.71)	70°F (21°C)
92.5 (69.0)	2285	7.34 (27.77)	0.547 (0.333)	12.60 (2.48)	Relative humidity
62.5 (46.6)	2310	5.81 (22.01)	0.641 (0.390)	10.76 (2.12)	45%
31.5 (23.5)	2330	4.15 (15.70)	0.907 (0.552)	7.60 (1.50)	Barometer
--	2345	2.78 (10.51)	--	--	29.6" Hg (100.2 kPa)

Maximum Torque - 539.7 lb.-ft. (731.8 Nm) at 1400 rpm

Maximum Torque rise - 61.8%

Torque rise at 1800 engine rpm - 42%

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—8th Gear									
107.0 (79.8)	10045 (44.69)	3.99 (6.43)	2203	6.0	0.609 (0.371)	11.42 (2.25)	183 (84)	81 (27)	29.5 (100.0)
75% of Pull at Maximum Power—8th Gear									
85.1 (63.5)	7530 (33.50)	4.24 (6.82)	2271	4.2	0.626 (0.380)	11.09 (2.18)	181 (83)	81 (27)	29.5 (100.0)
50% of Pull at Maximum Power—8th Gear									
57.3 (42.7)	5020 (22.32)	4.28 (6.89)	2293	3.2	0.795 (0.483)	8.75 (1.72)	179 (82)	73 (23)	29.5 (100.0)
75% of Pull at Reduced Engine Speed—9th Gear									
86.6 (64.6)	7510 (33.40)	4.32 (6.96)	1975	4.2	0.569 (0.346)	12.18 (2.40)	179 (82)	75 (24)	29.5 (100.0)
50% of Pull at Reduced Engine Speed—9th Gear									
59.4 (44.3)	5135 (22.85)	4.34 (6.98)	1941	3.6	0.675 (0.410)	10.30 (2.03)	178 (81)	72 (22)	29.5 (100.0)

Location of tests: HBLFA Francisco Josephinum
BLT Biomass-Logistics-Technology,
Rottenhauser, Strabe, 1, AT, 3250, Wieselburg,
Austria

Dates of tests: April - July, 2007.

Manufacturer: CNH Osterreich GmbH
SteyrerstraBe, 32, 4300, St. Valentin, Austria

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.829
Fuel weight 6.90 lbs/gal (0.827 kg/l) **Oil SAE**
10W30 **API service classification** CG-4
Transmission and hydraulic lubricant New
Holland Ambra Multi G fluid **Front axle lubricant**
New Holland Ambra Multi G fluid

ENGINE: Make CNH Diesel **Type** six cylinder
vertical with turbocharger and air to air intercooler
Serial No. 359098 **Crankshaft** lengthwise **Rated
engine speed** 2200 **Bore and stroke** 4.094" x
5.197" (104.0 mm x 132.0 mm) **Compression ratio**
16.5 to 1 **Displacement** 410 cu in (6728 ml) **Starting
system** 12 volt **Lubrication** pressure **Air cleaner**
two paper elements and aspirator **Oil filter** one full
flow cartridge **Oil cooler** engine coolant heat
exchanger for crankcase oil, radiator for hydraulic
and transmission oil **Fuel filter** two paper canisters
Muffler underhood **Exhaust** vertical **Cooling
medium temperature control** thermostat and
variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.**
Z6BH01009 **Tread width** rear 60.2" (1530 mm) to
87.8" (2230 mm) front 61.4" (1560 mm) to 89.0" (2260
mm) **Wheelbase** 113.5" (2884 mm) **Hydraulic
control system** direct engine drive **Transmission**
selective gear fixed ratio with full range operator
controlled powershift **Nominal travel speeds mph
(km/h)** first 1.21 (1.94) second 1.45 (2.33) third 1.74
(2.80) fourth 2.09 (3.36) fifth 2.52 (4.05) sixth 3.03
(4.87) seventh 3.49 (5.62) eighth 4.20 (6.76) ninth
5.05 (8.12) tenth 6.06 (9.76) eleventh 7.30 (11.75)
twelfth 8.78 (14.13) thirteenth 10.09 (16.24)
fourteenth 12.13 (19.52) fifteenth 14.57 (23.45)
sixteenth 17.52 (28.20) seventeenth 21.08 (33.92)
eighteenth 25.35 (40.79) nineteenth 25.35
(40.80) (1700 engine rpm) reverse 2.67 (4.30), 3.21
(5.16), 3.85 (6.20), 4.63 (7.45), 5.57 (8.96), 6.70
(10.78) **Clutch** multiple wet disc electro-
hydraulically operated by foot pedal **Brakes** wet
disc hydraulically operated by two foot pedals that
can be locked together **Steering** hydrostatic **Power
take-off** 540 rpm at 1950 engine rpm or 1000 rpm
at 2154 engine rpm **Unladen tractor mass** 17725
lb (8040 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Engaged)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. ^o F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
104.7 (78.1)	16345 (72.71)	2.40 (3.87)	2018	14.2	6th Gear 0.628 (0.382)	11.07 (2.18)	184 (84)	84 (29)	29.4 (99.5)
118.8 (88.6)	15750 (70.06)	2.83 (4.56)	2004	11.9	7th Gear 0.557 (0.339)	12.49 (2.46)	184 (84)	84 (29)	29.4 (99.5)
126.9 (94.6)	15245 (67.82)	3.12 (5.02)	1814	11.1	8th Gear 0.521 (0.317)	13.35 (2.63)	180 (82)	84 (29)	29.4 (99.5)
128.2 (95.6)	12495 (55.59)	3.85 (6.19)	1801	7.7	9th Gear 0.515 (0.313)	13.50 (2.66)	172 (78)	86 (30)	29.4 (99.5)
129.7 (96.7)	10315 (45.89)	4.72 (7.59)	1800	6.0	10th Gear 0.509 (0.310)	13.65 (2.69)	172 (78)	86 (30)	29.4 (99.5)
128.9 (96.1)	8685 (38.63)	5.57 (8.96)	1800	5.9	11th Gear 0.517 (0.314)	13.40 (2.65)	174 (79)	82 (28)	29.4 (99.5)
126.7 (94.5)	6995 (31.12)	6.79 (10.94)	1800	4.5	12th Gear 0.525 (0.319)	13.22 (2.60)	176 (80)	84 (29)	29.4 (99.5)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claims of 70.0 dB(A) cab sound level, 39.6 gpm (150 lpm) remote hydraulic flow nor 3 point lift capacity of 12787 lbs (5800 kg). The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2409** Nebraska Summary 624, November 24, 2008.

Roger M. Hoy
 Director

M.F. Kocher
 V.I. Adamchuk
 J.A. Smith
 Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 8th gear	72.0	72.0
Bystander	--	--

TIRES, BALLAST AND WEIGHT

Rear Tires - No., size, ply & psi(kPa)
Front Tires - No., size, ply & psi(kPa)
Height of Drawbar
Static Weight with operator - Rear
 - Front
 - Total

Tested without ballast

Two 710/70R38;**,15(100)
 Two 600/65R28;**,15(100)
 23.6 in (600 mm)
 10955 lb (4970 kg)
 6935 lb (3145 kg)
 17890 lb (8115 kg)

DRAWBAR PERFORMANCE
(Unballasted - Front Drive Disengaged)
FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—8th Gear									
108.5 (80.9)	10230 (45.51)	3.98 (6.40)	2206	7.2	0.606 (0.369)	11.47 (2.26)	176 (80)	75 (24)	29.7 (100.5)
75% of Pull at Maximum Power—8th Gear									
84.1 (62.7)	7690 (34.20)	4.10 (6.60)	2271	5.5	0.659 (0.401)	10.55 (2.08)	176 (80)	75 (24)	29.7 (100.5)
50% of Pull at Maximum Power—8th Gear									
57.0 (42.5)	5105 (22.70)	4.19 (6.74)	2295	4.6	0.809 (0.492)	8.59 (1.69)	180 (82)	75 (24)	29.7 (100.5)
75% of Pull at Reduced Engine Speed—9th Gear									
85.4 (63.7)	7700 (34.26)	4.16 (6.69)	1908	5.1	0.579 (0.353)	12.00 (2.37)	176 (80)	77 (25)	29.7 (100.5)
50% of Pull at Reduced Engine Speed—9th Gear									
57.7 (43.0)	5085 (22.63)	4.25 (6.84)	1929	4.2	0.692 (0.421)	10.05 (1.98)	174 (79)	77 (25)	29.7 (100.5)
MAXIMUM POWER IN SELECTED GEARS									
5th Gear									
76.7 (57.2)	12930 (57.52)	2.22 (3.58)	2266	14.2	0.766 (0.466)	9.08 (1.79)	181 (83)	73 (23)	29.7 (100.5)
6th Gear									
91.9 (68.5)	12920 (57.48)	2.67 (4.29)	2240	13.6	0.713 (0.434)	9.75 (1.92)	178 (81)	79 (26)	29.7 (100.5)
7th Gear									
102.1 (76.1)	12335 (54.86)	3.10 (4.99)	2206	11.5	0.637 (0.388)	10.91 (2.15)	180 (82)	79 (26)	29.6 (100.4)
8th Gear									
114.9 (85.7)	12490 (55.57)	3.45 (5.55)	2044	11.8	0.572 (0.348)	12.16 (2.40)	178 (81)	75 (24)	29.6 (100.4)
9th Gear									
122.6 (91.4)	12735 (56.65)	3.61 (5.81)	1812	13.3	0.541 (0.329)	12.84 (2.53)	176 (80)	73 (23)	29.6 (100.4)
10th Gear									
127.1 (94.8)	10455 (46.50)	4.56 (7.34)	1805	8.6	0.523 (0.318)	13.30 (2.62)	172 (78)	73 (23)	29.7 (100.5)
11th Gear									
110.8 (82.6)	7110 (31.63)	5.84 (9.40)	1810	7.0	0.587 (0.357)	11.83 (2.33)	172 (78)	73 (23)	29.7 (100.5)
12th Gear									
109.8 (81.9)	5890 (26.19)	6.99 (11.25)	1800	5.3	0.603 (0.367)	11.52 (2.27)	172 (78)	75 (24)	29.7 (100.5)

This vehicle is equipped with an electronically controlled engine Power management system that monitors and boosts engine power output in certain circumstances. This is achieved by electronically changing the characteristics of the engine power-speed curve. The engine Power management function ("boosted" power level) becomes active in the higher transmission gears (16th and above) and for road transport applications. The system is also activated when power transfer through the PTO exceeds a preset level (and forward speed exceeds 0.5 km/h), for mobile PTO driven implement applications. An override system is provided to enable PTO operations at the "boosted" power level while the vehicle is stationary for test purposes. The results of of this PTO output test are presented below.

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1022 rpm)					
172.1 (128.3)	2200	10.96 (41.47)	0.439 (0.267)	15.70 (3.09)	
Standard Power Take-off Speed - (1000 rpm)					
177.0 (132.0)	2153	10.94 (41.41)	0.426 (0.259)	16.18 (3.19)	
Maximum Power (1 hour)					
186.4 (139.0)	1900	10.99 (41.61)	0.407 (0.247)	16.96 (3.34)	

VARYING POWER AND FUEL CONSUMPTION

172.1 (128.3)	2200	10.96 (41.47)	0.439 (0.267)	15.70 (3.09)	Air temperature
149.0 (111.1)	2240	10.02 (37.95)	0.464 (0.282)	14.87 (2.93)	63°F (17°C)
113.3 (84.5)	2270	8.40 (31.81)	0.512 (0.312)	13.48 (2.66)	Relative humidity
76.4 (57.0)	2300	6.47 (24.50)	0.584 (0.355)	11.81 (2.33)	45%
38.6 (28.8)	2320	4.61 (17.45)	0.824 (0.501)	8.38 (1.65)	Barometer
--	2345	2.85 (10.80)	--	--	29.7"Hg (100.5 kPa)

Maximum Torque 579.1 lb.-ft. (785.1 Nm) at 1600 rpm

Maximum Torque Rise - 40.9%

Torque rise at 1800 rpm - 32%

HYDRAULIC PERFORMANCE

CATEGORY: IHN

Quick Attach: No

OECD Static test

Lift cylinders:

2 x 90 mm

Maximum force exerted through whole range: 10275 lbs (45.7 kN)

	<u>Standard pump</u>	<u>High flow pump</u>
i) Sustained pressure at compensator cutoff:	3175 psi (219 bar)	3175 psi (219 bar)
two outlet sets combined		
ii) Pump delivery rate at minimum pressure:	32.0 GPM (121.0 l/min)	39.1 GPM (148.1 l/min)
iii) Pump delivery rate at maximum		
hydraulic power:	27.0 GPM (102.0 l/min)	35.5 GPM (134.5 l/min)
Delivery pressure:	2830 psi (195 bar)	2610 psi (180 bar)
Power:	44.5 HP (33.2 kW)	54.2 HP (40.4 kW)
single outlet set		
ii) Pump delivery rate at minimum pressure:	26.2 GPM (99.3 l/min)	26.2 GPM (99.2 l/min)
iii) Pump delivery rate at maximum		
hydraulic power:	25.8 GPM (97.7 l/min)	25.7 GPM (97.4 l/min)
Delivery pressure:	2540 psi (175 bar)	2540 psi (175 bar)
Power:	38.2 HP (28.5 kW)	38.1 HP (28.4 kW)

THREE POINT HITCH PERFORMANCE (SAE Static test)

Observed maximum pressure psi. (bar)	3175 (219)				
Location:	lift cylinder				
Hydraulic oil temperature: °F (°C)	150 (65)				
Location:	hydraulic sump				
Category:	IHN				
Quick attach:	none				
System pressure 2865 psi (197 Bar) Lift cylinders - 2 x 90 mm					
Hitch point distance to ground level in. (mm)	19.7 (500)	21.9 (555)	25.8 (655)	33.7 (855)	45.3 (1150)
Lift force on frame lb	13195	13155	13195	13080	11690
" " " " " " (kN)	(58.7)	(58.5)	(58.7)	(58.2)	(52.0)

HITCH DIMENSIONS AS TESTED—NO LOAD

	OECD test		SAE test	
	inch	mm	inch	mm
A	31.9	810	31.5	800
B	17.9	454	17.9	454
C	15.1	383	15.1	383
D	14.6	372	14.6	372
E	10.9	277	10.9	277
F	10.6	270	10.6	270
G	36.4	925	36.4	925
H	2.4	60	2.4	60
I	19.7	440	19.7	440
J	25.8	655	25.8	655
K	26.9	682	26.9	682
L	48.2	1224	48.2	1224
M	23.1	587	23.1	587
N	38.3	974	38.3	974
O	9.0	230	19.7	500
P	52.8	1340	47.8	1214
Q	38.2	970	45.3	1150
R	40.2	1022	34.4	875

