

SUMMARY OF OECD TESTS 2814 & 2816 — NEBRASKA SUMMARY 947

NEW HOLLAND T4.105 DIESEL

12 SPEED

POWER TAKE-OFF PERFORMANCE (Tractor equipped with 2 post ROPS)

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.l/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed (PTO speed—642 rpm)					
94.4 (70.4)	2306	5.96 (22.55)	0.442 (0.269)	15.84 (3.12)	
Standard Power Take-off speed (538 rpm)					
96.7 (72.1)	1930	5.71 (21.62)	0.413 (0.251)	16.95 (3.34)	
VARYING POWER AND FUEL CONSUMPTION					
94.4 (70.4)	2306	5.96 (22.55)	0.442 (0.269)	15.84 (3.12)	Air temperature
81.0 (60.4)	2328	5.39 (20.41)	0.465 (0.283)	15.02 (2.96)	63°F (17°C)
61.2 (45.6)	2347	4.35 (16.47)	0.497 (0.302)	14.07 (2.77)	Relative humidity
41.3 (30.8)	2374	3.41 (12.89)	0.577 (0.351)	12.13 (2.39)	71%
20.8 (15.5)	2391	2.36 (8.95)	0.796 (0.484)	8.78 (1.73)	Barometer
--	2401	1.54 (5.84)	--	--	30.0" Hg (101.5 kPa)
Maximum torque -302.2 lb.-ft. (409.7 Nm) at 1486 rpm					
Maximum torque rise -40.6%					
Torque rise at 1840 engine rpm -27%					
Power increase at 1930 rpm -2.4%					

POWER TAKE-OFF PERFORMANCE (Tractor equipped with Cab)

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.l/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed (PTO speed—641 rpm)					
94.5 (70.5)	2301	5.96 (22.55)	0.440 (0.268)	15.89 (3.13)	
Standard Power Take-off speed (540 rpm)					
96.6 (72.0)	1938	5.72 (21.64)	0.414 (0.252)	16.90 (3.33)	
VARYING POWER AND FUEL CONSUMPTION					
94.5 (70.5)	2301	5.96 (22.55)	0.440 (0.268)	15.89 (3.13)	Air temperature
81.3 (60.6)	2326	5.43 (20.55)	0.467 (0.284)	14.97 (2.95)	67°F (19°C)
61.4 (45.8)	2345	4.39 (16.61)	0.499 (0.304)	14.01 (2.76)	Relative humidity
41.4 (30.9)	2372	3.43 (13.00)	0.579 (0.352)	12.08 (2.38)	67%
20.9 (15.6)	2389	2.38 (9.02)	0.798 (0.486)	8.76 (1.73)	Barometer
--	2399	1.57 (5.94)	--	--	30.1" Hg (101.8 kPa)
Maximum torque -303.4 lb.-ft. (411.4 Nm) at 1488 rpm					
Maximum torque rise -40.5%					
Torque rise at 1840 engine rpm -26%					
Power increase at 1938 rpm -2.2%					

Location of tests: Alma Mater Studiorum, University Di Bologna, Via Gandolfi, 19-40057, Cadriano, Bologna, Italy

Dates of tests: August to December, 2013

Manufacturer: CNH Italia SpA, Viale delle Nazioni 55, Modena, Italy

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.840 **Fuel weight** 6.99 lbs/gal (0.838 kg/l) **Oil** SAE 15W40 **API service classification** CJ-4 **Transmission and hydraulic lubricant** Akcela Nexplore fluid **Front axle lubricant** Akcela Nexplore fluid

ENGINE: Make FPT Industrial Diesel **Type** four cylinder vertical with turbocharger and air to air intercooler **Serial No.** 000136201 **Crankshaft** lengthwise **Rated engine speed** 2300 **Bore and stroke** 3.898" x 4.331" (99.0 mm x 110.0 mm) **Compression ratio** 17.1 to 1 **Displacement** 207 cu in (3387 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Exhaust** regenerative particulate filter integrated within an underhood muffler with vertical outlet **Cooling medium temperature control** thermostat

CHASSIS: **Type** front wheel assist **Serial No.** ZDJX 50765 **Tread width** rear 52.6" (1337 mm) to 76.3" (1937 mm) front 48.6" (1235 mm) to 76.3" (1937 mm) **Wheel base** 88.9" (2258 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio **Nominal travel speeds mph (km/h)** first 1.34 (2.15) second 1.99 (3.20) third 2.95 (4.74) fourth 3.12 (5.02) fifth 4.32 (6.95) sixth 4.64 (7.47) seventh 6.87 (11.06) eighth 7.34 (11.82) ninth 10.09 (16.24) tenth 10.94 (17.60) eleventh 16.18 (26.04) twelfth 23.75 (38.22) reverse 1.31 (2.11), 1.95 (3.15), 2.89 (4.66), 3.07 (4.94), 4.23 (6.81), 4.57 (7.35), 6.76 (10.88), 7.22 (11.63), 9.92 (15.96), 10.75 (17.30), 15.91 (25.60), 23.36 (37.58) **Clutch** dual dry disc operated by foot pedal **Brakes** wet disc hydraulically operated by two foot pedals which can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1938 engine rpm or 1000 rpm at 1926 engine rpm **Unladen tractor mass** w/2 post ROPS - 7595 lbs (3445 kg), w/cab - 8400 lb (3810 kg)

**T4.105 - with 2 post ROPS
(Unballasted - Front Drive Engaged)**

DRAWBAR PERFORMANCE

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption		Temp.°F (°C)	Barom. inch Hg (kPa)	
					lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	cool- ing med	Air dry bulb	
Maximum Power—7th(3M)Gear									
59.8 (44.6)	3490 (15.53)	6.43 (10.34)	2302	7.4	0.589 (0.358)	11.88 (2.34)	199 (93)	46 (8)	29.9 (101.4)
75% of Pull at Maximum Power—7th(3M) Gear									
46.1 (34.4)	2615 (11.65)	6.61 (10.63)	2331	5.7	0.666 (0.405)	10.51 (2.07)	199 (93)	45 (7)	29.9 (101.4)
50% of Pull at Maximum Power—7th(3M)Gear									
31.4 (23.4)	1745 (7.77)	6.74 (10.85)	2356	4.8	0.830 (0.505)	8.43 (1.66)	201 (94)	45 (7)	29.9 (101.4)
75% of Pull at Reduced Engine Speed—8th(1H) Gear									
46.2 (34.4)	2620 (11.65)	6.61 (10.63)	2176	5.6	0.586 (0.356)	11.94 (2.35)	199 (93)	45 (7)	29.9 (101.4)
50% of Pull at Reduced Engine Speed—8th(1H) Gear									
31.4 (23.4)	1745 (7.77)	6.75 (10.85)	2208	4.7	0.721 (0.438)	9.71 (1.91)	199 (93)	43 (6)	29.9 (101.4)

MAXIMUM POWER IN SELECTED GEARS

6th(2M)Gear									
60.5 (45.1)	6265 (27.87)	3.62 (5.83)	2102	15.0	0.610 (0.371)	11.47 (2.26)	199 (93)	52 (11)	29.9 (101.4)
7th(3M)Gear									
75.2 (56.1)	5465 (24.32)	5.16 (8.31)	1943	11.6	0.514 (0.313)	13.60 (2.68)	199 (93)	52 (11)	29.9 (101.4)
8th(1H) Gear									
76.8 (57.3)	5140 (22.86)	5.60 (9.02)	1938	10.0	0.505 (0.307)	13.86 (2.73)	201 (94)	50 (10)	29.9 (101.4)
9th(4M) Gear									
76.7 (57.2)	3630 (16.14)	7.93 (12.76)	1946	7.5	0.506 (0.308)	13.81 (2.72)	201 (94)	48 (9)	29.9 (101.4)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's remote hydraulic flow claims of 12.5 GPM (47.5 l/min) for standard pump nor 16.9 GPM (64.0 l/min) with optional pump. This tractor did not meet the manufacturer's 3 point lift capacity claim of 5620 lbs (2549 kg). The manufacturer's 3 point lift claim of 7351 lbs (3334 kg) with optional lift ram was not verified. The performance results on this summary were taken from tests conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Reports No. **2814** and **2816**, Nebraska Summary 947, July 11, 2014.

Roger M. Hoy
Director

M.F. Kocher
S. Pitla
P.J. Jasa
Board of Tractor Test Engineers

TIRES AND WEIGHT

Rear tires—No., size, ply & psi (kPa)
Front tires—No., size, ply & psi (kPa)
Height of drawbar
Static weight with operator—Rear
— Front
— Total

Tested without ballast

Two 540/65R34;**,23 (160)
Two 440/65R24;**,23 (160)
18.1 in (460 mm)
4640 lb (2105 kg)
3120 lb (1415 kg)
7760 lb (3520 kg)

T4.105 - with cab
(Unballasted - Front Drive Engaged)

DRAWBAR PERFORMANCE
FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption		Temp. °F (°C)	Barom. inch Hg (kPa)	
					lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	cool- ing med	Air dry bulb	
Maximum Power—7th (3M) Gear									
61.0 (45.5)	3515 (15.63)	6.51 (10.48)	2302	6.0	0.604 (0.368)	11.57 (2.28)	194 (90)	39 (4)	29.9 (101.1)
75% of Pull at Maximum Power—7th(3M) Gear									
47.2 (35.2)	2635 (11.72)	6.72 (10.82)	2335	4.5	0.675 (0.410)	10.37 (2.04)	196 (91)	41 (5)	29.9 (101.1)
50% of Pull at Maximum Power—7th(3M) Gear									
32.1 (23.9)	1755 (7.82)	6.85 (11.03)	2362	3.5	0.815 (0.496)	8.58 (1.69)	194 (90)	39 (4)	29.9 (101.1)
75% of Pull at Reduced Engine Speed—8th(1H) Gear									
47.2 (35.2)	2635 (11.72)	6.72 (10.82)	2188	4.4	0.594 (0.361)	11.78 (2.32)	196 (91)	39 (4)	29.9 (101.1)
50% of Pull at Reduced Engine Speed—8th(1H) Gear									
32.1 (23.9)	1755 (7.82)	6.85 (11.03)	2207	3.5	0.730 (0.444)	9.58 (1.89)	194 (90)	39 (4)	29.9 (101.1)

MAXIMUM POWER IN SELECTED GEARS

6th(2M) Gear									
65.4 (48.8)	6755 (30.05)	3.63 (5.85)	2102	15.0	0.596 (0.362)	11.74 (2.31)	194 (90)	41 (5)	29.9 (101.1)
7th(3M) Gear									
76.4 (57.0)	5405 (24.04)	5.30 (8.54)	1976	10.7	0.505 (0.307)	13.86 (2.73)	196 (91)	41 (5)	29.9 (101.1)
8th(1H) Gear									
77.5 (57.8)	5080 (22.59)	5.72 (9.21)	1962	9.4	0.500 (0.304)	13.97 (2.75)	196 (91)	41 (5)	29.9 (101.1)
9th(4M) Gear									
77.4 (57.7)	3585 (15.95)	8.10 (13.03)	1956	6.1	0.503 (0.306)	13.91 (2.74)	194 (90)	43 (6)	29.9 (101.1)

TIRES AND WEIGHT

Rear tires—No., size, ply & psi (kPa)
Front tires—No., size, ply & psi (kPa)
Height of drawbar
Static weight with operator—Rear
 — Front
 — Total

Tested without ballast

Two 540/65R34; **,23 (160)
 Two 440/65R24; **,23 (160)
 18.1 in (460 mm)
 5025 lb (2280 kg)
 3540 lb (1605 kg)
 8565 lb (3885 kg)

TRACTOR SOUND LEVEL WITHOUT CAB	FWA dB(A)	2WD dB(A)
At no load in 6th (2M) gear	82.0	82.0
Bystander	--	--

TRACTOR SOUND LEVEL WITH CAB	FWA dB(A)	2WD dB(A)
At no load in 6th (2M) gear	76.5	76.5
Bystander	--	--

HYDRAULIC PERFORMANCE

CATEGORY: II

Quick Attach: None

OECD Static test

Maximum force exerted through whole range:	3520 lbs (15.6 kN)	
	<u>Standard pump</u>	<u>Optional pump</u>
i) Sustained pressure with relief valve open:	2800 psi (193 bar)	2845 psi (196 bar)
ii) Pump delivery rate at minimum pressure:	11.6 GPM (44.0 l/min)	14.9 GPM (56.5 l/min)
iii) Pump delivery rate at maximum		
hydraulic power:	10.7 GPM (40.5 l/min)	13.4 GPM (50.8 l/min)
Delivery pressure:	2555 psi (176 bar)	2525 psi (174 bar)
Power:	16.0 hp (11.9 kW)	19.7 hp (14.7 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	25.6	650
B	10.0	255
C	13.9	352
D	11.7	296
E	10.0	255
F	8.3	210
G	29.5	750
H	0.6	15
I	15.2	385
J	21.2	540
K	17.9	455
L	42.6	1083
M	22.0	558
N	37.5	953
O	13.5	343
P	45.3	1150
Q	42.8	1088
R	21.6	545

