

# NEBRASKA TRACTOR TEST 1836

## NEW HOLLAND TC 48DA DIESEL

### 12 SPEED

#### POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
---------------------	--------------------------------	-----------------	-----------------------	-----------------------	--------------------------------

#### MAXIMUM POWER AND FUEL CONSUMPTION

Rated Engine Speed—(PTO speed—611 rpm)					
40.98 (30.56)	2800	3.36 (12.72)	0.576 (0.350)	12.19 (2.40)	
Standard Power Take-off Speed(540 rpm)					
38.56 (28.75)	2477	2.95 (11.18)	0.538 (0.327)	13.06 (2.57)	

#### VARYING POWER AND FUEL CONSUMPTION

40.98 (30.56)	2800	3.36 (12.72)	0.576 (0.350)	12.19 (2.40)	Air temperature
36.61 (27.30)	2941	3.03 (11.48)	0.582 (0.354)	12.07 (2.38)	77°F (25°C)
27.97 (20.86)	2980	2.39 (9.06)	0.601 (0.365)	11.69 (2.30)	Relative humidity
18.74 (13.97)	3006	1.92 (7.28)	0.720 (0.438)	9.75 (1.92)	26%
9.36 (6.98)	3027	1.45 (5.50)	1.090 (0.663)	6.44 (1.27)	Barometer
0.63 (0.47)	3044	1.11 (4.21)	12.339 (7.506)	0.57 (0.11)	28.86"Hg (97.73 kPa)

Maximum torque 96 lb.-ft. (130 Nm) at 1602 rpm  
 Maximum torque rise -24.8%  
 Torque rise at 2206 rpm - 14%

#### TRACTOR SOUND LEVEL WITHOUT CAB

At no load in 7th (M3) gear	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
Bystander	92.0	92.0
	--	--

#### TIRES AND WEIGHT

**Rear Tires**—No., size, ply & psi (kPa)  
**Front Tires**—No., size, ply & psi (kPa)  
**Height of Drawbar**  
**Static Weight with operator**—Rear  
     — Front  
     — Total

#### Tested Without Ballast

Two 18.4-24; 8:12 (85)  
 Two 12-16.5; 8:12 (85)  
 17.0 in (405 mm)  
 2650 lb (1202 kg)  
 1840 lb (835 kg)  
 4490 lb (2037 kg)

**Location of Test:** Nebraska Tractor Test Laboratory, University of Nebraska, Lincoln Nebraska 68583-0832

**Dates of Test:** April 27-30, 2004

**Manufacturer:** CNH America LLC, 700 State Street, Racine, Wi. 53404

**FUEL, OIL and TIME:** Fuel No. 2 Diesel Specific gravity converted to 60°/60° F (15°/15°C) 0.8432 Fuel weight 7.021 lbs/gal (0.841 kg/l) Oil SAE 15W40 API service classification CF-4/SG Transmission and hydraulic lubricant New Holland M2C134D fluid Front axle lubricant New Holland M2C134D fluid Total time engine was operated 12.5 hours

**ENGINE:** Make ISM Diesel Type four cylinder vertical Serial No. 28854 Crankshaft lengthwise Rated engine speed 2800 Bore and stroke 3.307" x 3.937" (84.0 mm x 100.0 mm) Compression ratio 22.4 to 1 Displacement 135 cu in (2216 ml) Starting system 12 volt Lubrication pressure Air cleaner two paper elements Oil filter one full flow cartridge Oil cooler engine coolant heat exchanger for crankcase oil Fuel filter one paper element Muffler underhood Exhaust horizontal Cooling medium temperature control one thermostat

**ENGINE OPERATING PARAMETERS:** Fuel rate: 21.6 - 23.8 lb/h (9.8 - 10.8 kg/h) High idle: 2950 - 3050 rpm

**CHASSIS:** Type front wheel assist Serial No. HV10007 Tread width rear 52.8" (1341 mm) to 76.3" (1939 mm) front 56.4" (1432 mm) Wheelbase 74.8" (1900 mm) Hydraulic control system direct engine drive Transmission selective gear fixed ratio Nominal travel speeds mph (km/h) first 1.12 (1.81) second 1.52 (2.45) third 1.99 (3.21) fourth 2.56 (4.12) fifth 2.83 (4.56) sixth 3.84 (6.18) seventh 5.03 (8.09) eighth 6.45 (10.38) ninth 7.98 (12.84) tenth 10.81 (17.39) eleventh 14.14 (22.76) twelfth 18.15 (29.21) reverse 1.21 (1.95), 1.64 (2.64), 2.09 (3.36), 2.76 (4.44), 3.05 (4.91), 4.13 (6.65), 5.41 (8.70), 6.94 (11.17), 8.58 (13.81), 11.63 (18.71), 15.09 (24.29), 19.53 (31.43) Clutch single dry disc operated by foot pedal Brakes single wet disc operated by two foot pedals which can be locked together Steering hydrostatic Power take-off 540 rpm at 2475 engine rpm Unladen tractor mass 4315 lb (1957 kg)

### THREE POINT HITCH PERFORMANCE (OECD Static Test)

CATEGORY: I, II

Quick Attach: None

Maximum Force Exerted Through Whole Range:	2776 lbs (12.3 kN) Category I
	2430 lbs (10.8 kN) Category II
i) Opening pressure of relief valve:	NA
Sustained pressure of the open relief valve:	2460 psi (170 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed:	11.2 GPM (42.5 l/min)
iii) Pump delivery rate at maximum	
hydraulic power:	11.3 GPM (42.9 l/min)
Delivery pressure:	1735 psi (120 bar)
Power:	11.5 HP (8.6 kW)

### THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi. (bar)	2565 (177)
Location:	lift cylinder
Hydraulic oil temperature: °F (°C)	178 (81)
Location:	hydraulic sump
Category:	I, II
Quick attach:	none

#### Category I

SAE Static Test—System pressure 2320 psi (160 Bar)

Hitch point distance to ground level in. (mm)	8.0 (203)	14.0 (356)	20.1 (511)	25.9 (658)	32.1 (815)
Lift force on frame lb	3832	3647	3433	3180	2789
" " " " " " (kN)	(17.0)	(16.2)	(15.3)	(14.1)	(12.4)


#### Category II

SAE Static Test—System pressure 2320 psi (160 Bar)

Hitch point distance to ground level in. (mm)	8.2 (208)	15.2 (386)	22.0 (559)	29.0 (737)	35.9 (912)
Lift force on frame lb	3439	3356	3143	2892	2305
" " " " " " (kN)	(15.3)	(14.9)	(14.0)	(12.9)	(10.3)

	Category I		Category II	
	inch	mm	inch	mm
A	23.1	587	23.0	584
B	11.8	300	11.8	300
C	13.5	344	13.5	344
D	13.5	342	13.5	342
E	10.3	262	10.3	262
F	5.2	132	5.2	132
G	26.0	660	26.0	660
H	0.5	13	0.5	13
I	12.2	309	12.2	309
J	20.8	528	20.8	528
K	14.2	362	14.2	361
L	34.6	879	34.5	876
M	22.9	582	22.8	579
N	31.5	800	31.4	797
O	6.6	168	6.9	175
P	38.9	988	39.9	1013
Q	34.1	865	34.5	876
R	21.4	543	21.4	543

HITCH DIMENSIONS AS TESTED - NO LOAD



**REPAIRS AND ADJUSTMENTS:** No repairs or adjustments

**REMARKS:** All test results were determined from observed data obtained in accordance with official OECD, SAE and Nebraska test procedures. This tractor did not meet the manufacturer's claims of 3465 lb (1571 kg) 3 point hitch lift at 24" nor 12.0 GPM (45.5 lpm) hydraulic flow. For the maximum power tests, the fuel temperature at the injection pump inlet was maintained at 104°F (40°C).

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. **1836**, November 1, 2004

Leonard L. Bashford  
Director

M.F. Kocher  
V.I. Adamchuk  
W.P. Campbell  
Board of Tractor Test Engineers



New Holland TC 48DA Diesel