

NEBRASKA OECD TRACTOR TEST 2068—SUMMARY 886

VERSATILE 400 DIESEL

16 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1000 rpm)					
330.93 (246.78)	2106	22.21 (84.06)	0.472 (0.287)	14.90 (2.94)	Fuel used during active exhaust regeneration - 0.16 gal (0.60 l) (see Note 1 p.2)
Standard Power Take-off Speed—(PTO speed—1000 rpm)					
330.93 (246.78)	2106	22.21 (84.06)	0.472 (0.287)	14.90 (2.94)	
Maximum Power (1 hour)					
390.50 (291.19)	1750	22.11 (83.70)	0.398 (0.242)	17.66 (3.48)	

VARYING POWER AND FUEL CONSUMPTION

330.93 (246.78)	2106	22.21 (84.06)	0.472 (0.287)	14.90 (2.94)	Air temperature
286.82 (213.88)	2145	19.42 (73.50)	0.476 (0.289)	14.77 (2.91)	81°F (27°C)
218.01 (162.57)	2175	16.47 (62.34)	0.531 (0.323)	13.24 (2.61)	Relative humidity
146.93 (109.56)	2198	13.20 (49.97)	0.632 (0.384)	11.13 (2.19)	60%
73.35 (54.70)	2200	10.13 (38.33)	0.970 (0.590)	7.24 (1.43)	Barometer
5.68 (4.24)	2199	6.56 (24.83)	8.114 (4.936)	0.87 (0.17)	28.72" Hg (97.26 kPa)

Maximum Torque - 1396 lb.-ft. (1893 Nm) at 1400 rpm
 Maximum Torque Rise - 69.1%
 Torque rise at 1680 engine rpm - 47%
 Power increase at 1750 engine rpm - 18.0%

DRAWBAR PERFORMANCE (Unballasted)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp. °F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—6th Gear									
317.27 (236.58)	21337 (94.91)	5.58 (8.98)	2100	2.8	0.493 (0.300)	14.27 (2.81)	190 (88)	77 (25)	28.72 (97.26)
75% of Pull at Maximum Power—6th Gear									
245.92 (183.38)	16005 (71.19)	5.76 (9.27)	2157	2.3	0.530 (0.323)	13.25 (2.61)	190 (88)	88 (31)	28.72 (97.26)
50% of Pull at Maximum Power—6th Gear									
167.81 (125.14)	10670 (47.46)	5.90 (9.50)	2192	1.6	0.599 (0.364)	11.74 (2.31)	188 (87)	91 (33)	28.71 (97.22)
75% of Pull at Reduced Engine Speed—9th Gear									
245.23 (182.87)	15910 (70.77)	5.78 (9.30)	1516	2.3	0.438 (0.267)	16.04 (3.16)	190 (88)	90 (32)	28.71 (97.22)
50% of Pull at Reduced Engine Speed—9th Gear									
167.70 (125.05)	10646 (47.35)	5.91 (9.51)	1538	1.5	0.481 (0.293)	14.61 (2.88)	187 (86)	91 (33)	28.71 (97.22)

Location of Tests: Nebraska Tractor Test Laboratory, University of Nebraska, Lincoln, Nebraska 68583-0832

Dates of Test: August 27- September 5, 2013

Manufacturer: Buhler Versatile, 1260 Clarence Ave Winnipeg, Manitoba, Canada R3T 1T2

FUEL, OIL and TIME: Fuel No. 2 Diesel Specific gravity converted to 60°/60°F (15°/15°C) 0.8442 Fuel weight 7.029 lbs/gal (0.842 kg/l) Oil SAE 15W-40 API service classification CJ-4 Transmission, hydraulic and final drive lubricant Hydraul 56 fluid Total time engine was operated: 25.0 hours

ENGINE: Make Cummins Diesel **Type** six cylinder vertical with turbocharger and air to air intercooler **Serial No.** *75018140* **Crankshaft** lengthwise **Rated engine speed** 2100 **Bore and stroke** 5.118" x 5.906" (130.0 mm x 150.0 mm) **Compression ratio** 16.6 to 1 **Displacement** 729 cu in (11946 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements and aspirator **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic oil, radiator for transmission, front and rear axle oil **Fuel filter** two paper cartridges **Fuel cooler** radiator for returned fuel **Exhaust** regenerative particulate filter integrated within a vertical muffler **Cooling medium temperature control** thermostat

ENGINE OPERATING PARAMETERS: Fuel rate: 142.9 - 157.5 lb/h (64.8 - 71.4 kg/h) **High idle:** 2150 - 2250 rpm **Turbo boost:** nominal 27.6 - 33.4 psi (190 - 230 kPa) as measured 30.4 psi (210 kPa)

CHASSIS: Type four wheel drive with duals **Serial No.** *307322* **Tread width** rear 72.0" (1828 mm) and 124.9" (3171 mm), front 72.0" (1828 mm) and 124.9" (3171 mm) **Wheelbase** 135.0" (3430 mm) **Hydraulic control system** direct engine drive **Transmission** selective gear fixed ratio with full range operator controlled power shift **Nominal travel speeds mph (km/h)** first 2.06 (3.32) second 2.62 (4.21) third 3.31 (5.33) fourth 4.21 (6.77) fifth 5.01 (8.06) sixth 5.64 (9.07) seventh 6.36 (10.23) eighth 7.16 (11.52) ninth 8.05 (12.95) tenth 9.06 (14.58) eleventh 10.22 (16.45) twelfth 11.51 (18.52) thirteenth 13.70 (22.05) fourteenth 17.40 (28.00) fifteenth 20.44 (32.90) sixteenth 22.97 (36.96) electronically limited reverse 1.65 (2.65), 4.01 (6.45), 4.51 (7.26), 10.96 (17.64)

DRAWBAR PERFORMANCE

(Unballasted at 2100 rpm)

MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
2nd Gear									
232.28 (173.21)	37041 (164.77)	2.36 (3.79)	2145	13.9	0.588 (0.358)	11.95 (2.36)	189 (87)	76 (24)	28.73 (97.29)
3rd Gear									
294.62 (219.70)	35686 (158.74)	3.10 (4.99)	2104	8.5	0.536 (0.326)	13.11 (2.58)	190 (88)	79 (26)	28.72 (97.26)
4th Gear									
306.10 (228.26)	28060 (124.81)	4.09 (6.58)	2099	4.5	0.512 (0.311)	13.73 (2.70)	190 (88)	83 (29)	28.73 (97.29)
5th Gear									
314.82 (234.76)	23973 (106.64)	4.92 (7.92)	2099	3.6	0.495 (0.301)	14.19 (2.80)	190 (88)	81 (27)	28.73 (97.29)
6th Gear									
317.27 (236.58)	21337 (94.91)	5.58 (8.98)	2100	2.8	0.493 (0.300)	14.27 (2.81)	190 (88)	77 (25)	28.72 (97.26)
7th Gear									
317.23 (236.55)	18853 (83.86)	6.31 (10.15)	2100	2.5	0.496 (0.302)	14.18 (2.79)	189 (87)	79 (26)	28.73 (97.29)
8th Gear									
317.68 (236.89)	16733 (74.43)	7.12 (11.46)	2101	2.3	0.497 (0.302)	14.14 (2.79)	190 (88)	79 (26)	28.64 (96.99)
9th Gear									
313.33 (233.65)	14645 (65.14)	8.03 (12.91)	2100	2.1	0.499 (0.304)	14.09 (2.77)	190 (88)	80 (27)	28.64 (96.99)

Clutch wet multiple disc hydraulically actuated by foot pedal **Brakes** single dry caliper per axle hydraulically actuated foot pedal **Steering** hydrostatic and articulated **Power take-off** 1000 rpm at 2105 engine rpm **Unladen tractor mass** 37325 lb (16930 kg)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

NOTE. The manufacturer declares that the average time between active regenerations is 36 hours, while operated in Auto Filter Cleaning Mode, at rated speed, full PTO load, under steady state conditions.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD, SAE and Nebraska test procedures. This tractor did not meet the manufacturer's remote hydraulic flow claim of 58 GPM (220 l/m) with the standard pump. The manufacturer's remote hydraulic flow claim of 113 GPM (428 l/m), with high flow system, was not verified. For the maximum power tests the fuel temperature at the primary fuel filter was maintained at 130°F (55°C). The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. **2068**, Nebraska Summary 886, November 25, 2013.

Roger M. Hoy
Director

M.F. Kocher
P.J. Jasa
J.D. Luck
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB

dB(A)

At no load in 5th gear	72.4
Bystander in 14th gear	88.0

TIRES AND WEIGHT

Rear Tires - No., size, ply & psi(kPa)

Front Tires - No., size, ply & psi(kPa)

Height of Drawbar

Static Weight with operator - Rear

- Front

- Total

Tested Without Ballast

Four 480/80R46;***;12(85)

Four 480/80R46;***;20(135)

23.0 in (585 mm)

14600 lb (6623 kg)

22900 lb(10387 kg)

37500 lb(17010 kg)

DRAWBAR PERFORMANCE
(Unballasted at 1750 RPM)
MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Fuel Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
2nd Gear									
233.06 (173.79)	37044 (164.78)	2.36 (3.79)	2145	13.5	0.583 (0.355)	12.05 (2.37)	189 (87)	75 (24)	28.72 (97.26)
3rd Gear									
295.14 (220.09)	35743 (158.99)	3.10 (4.99)	2103	8.6	0.535 (0.326)	13.13 (2.59)	190 (88)	78 (25)	28.73 (97.29)
4th Gear									
330.99 (246.52)	34327 (152.69)	3.62 (5.82)	1914	7.4	0.484 (0.294)	14.53 (2.86)	190 (88)	84 (29)	28.73 (97.29)
5th Gear									
352.75 (263.04)	31756 (141.26)	4.17 (6.70)	1823	6.0	0.454 (0.276)	15.47 (3.05)	190 (88)	85 (29)	28.72 (97.26)
6th Gear									
360.67 (268.95)	29759 (132.37)	4.55 (7.31)	1750	5.2	0.435 (0.265)	16.14 (3.18)	191 (88)	82 (28)	28.73 (97.29)
7th Gear									
367.35 (273.93)	26570 (118.19)	5.18 (8.34)	1749	3.9	0.431 (0.262)	16.33 (3.22)	190 (88)	78 (25)	28.73 (97.29)
8th Gear									
367.42 (273.99)	23461 (104.36)	5.87 (9.45)	1749	3.3	0.431 (0.262)	16.30 (3.21)	191 (88)	78 (25)	28.64 (96.99)
9th Gear									
364.08 (271.49)	20592 (91.60)	6.63 (10.67)	1750	2.9	0.431 (0.262)	16.30 (3.21)	191 (88)	81 (27)	28.64 (96.99)
10th Gear									
366.29 (273.14)	18340 (81.58)	7.49 (12.05)	1750	2.5	0.429 (0.261)	16.40 (3.23)	191 (88)	82 (28)	28.64 (96.99)
11th Gear									
363.30 (270.91)	16077 (71.51)	8.48 (13.64)	1750	2.2	0.435 (0.265)	16.16 (3.18)	192 (89)	82 (28)	28.64 (96.99)

HYDRAULIC PERFORMANCE


CATEGORY: 4N
 Quick Attach: Yes
 OECD Static test

Maximum force exerted through whole range:	13152 lbs(58.5kN)
	Standard pump
	<u>three outlet sets combined</u>
i) Sustained pressure at compensator cutoff:	2890 psi (199 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed:	53.1 GPM(201.0l/min)
iii) Pump delivery rate at maximum hydraulic power:	52.2 GPM(197.5l/min)
Delivery pressure:	2611 psi (180 bar)
Power:	79.5 HP (59.2kW)
	<u>single outlet set</u>
i) Sustained pressure at compensator cutoff:	2883 psi (199 bar)
ii) Pump delivery rate at minimum pressure and rated engine speed:	35.0 GPM(132.5l/min)
iii) Pump delivery rate at maximum hydraulic power:	33.7 GPM(127.7 l/min)
Delivery pressure:	2264 psi (156 bar)
Power:	44.5 HP (33.2kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	27.2	690
B	19.3	490
C	20.1	510
D	18.6	472
E	11.9	302
F	10.7	273
G	36.2	920
H	0.5	13
I	25.7	652
J	25.5	647
K	25.0	635
L	53.7	1364
*L'	60.4	1534
M	23.6	599
N	43.0	1093
O	9.1	230
P	53.0	1347
Q	43.5	1105
R	34.3	870

*L' to Quick Attach ends



VERSATILE 400 DIESEL